

الصين ليزر الباركود بلوتوث المحمولة ماسح الباركود مع ذاكرة YT-890

Yumite



Description

Yumite

الماسح الضوئي barcode Yumite

والتصميم الجميل، الخارجية تحميها لينة من المطاط والداخلية العلمي Exquisite a.

هيكل التصلب، حتى المقاومة انخفاض له أفضل من الماسح الضوئي العادي.

يتم تطبيق ب. يتوجب أحدث الإنجاز التقني لوظيفة المحرك وفك التشفير، قراءة

رموز بشكل أفضل وأسرع من نوع مماثل في السوق.

c.Easy باستخدام، الإعداد السهل.

.وارتفاع 1.5 مرة من الماسح الضوئي العادي، فإنه يضمن استخدام قتا أطول بعد مشحونة بالكامل، d.Large القدرة


Feature

Yumite

- يدعم معيار بروتوكولات بلوتوث؛ لا التحويلات أو محولات الحاجة؛
- ووصلة بلوتوث لاسلكي ممكن USB2.0 بار كود الضوئي عن طريق اتصال كابل
- وقد تم تجهيز وحدة مع أقراص، والأجهزة المحمولة وأجهزة الكمبيوتر المحمولة
- دائرة الرقابة الداخلية الدعم، ماك، الروبوت، والهواتف الذكية، XP / 08/07 دعم مايكروسوفت ويندوز
- المساعد الشخصي الرقمي وهلم جرا
- الباركود storage500-10000 التحقق من الوضع " هو بسيط، ويمكن استخدامها بسهولة، ويمكن "
- (اعتمادا على بيئة العمل) M تحت عنوان "الوضع العادي" مسافة الإرسال هو 20 ~ 50

| Para | Model | YT-890 | | | | | | | | | | | | | | | | | | |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------|----------------------|-------|------|----------------------|-------|------|------------------------|-------|------|-----------------------|-------|------|-------------------------|-------|------|------------------------|-------|
| Image | | | | | | | | | | | | | | | | | | | | |
| Image | | | | | | | | | | | | | | | | | | | | |
| Performance Parameter | | | | | | | | | | | | | | | | | | | | |
| Depth Filed | <table border="1"> <tr> <td>20mm</td> <td>EAN13(10mil,13bytes)</td> <td>250mm</td> </tr> <tr> <td>15mm</td> <td>code39(10mil,6bytes)</td> <td>260mm</td> </tr> <tr> <td>40mm</td> <td>code39(15.6mil,6bytes)</td> <td>350mm</td> </tr> <tr> <td>15mm</td> <td>code128(10mil,6bytes)</td> <td>270mm</td> </tr> <tr> <td>20mm</td> <td>code128(15.6mil,6bytes)</td> <td>330mm</td> </tr> <tr> <td>30mm</td> <td>EAN13(15.6mil,13bytes)</td> <td>360mm</td> </tr> </table> | | 20mm | EAN13(10mil,13bytes) | 250mm | 15mm | code39(10mil,6bytes) | 260mm | 40mm | code39(15.6mil,6bytes) | 350mm | 15mm | code128(10mil,6bytes) | 270mm | 20mm | code128(15.6mil,6bytes) | 330mm | 30mm | EAN13(15.6mil,13bytes) | 360mm |
| 20mm | EAN13(10mil,13bytes) | 250mm | | | | | | | | | | | | | | | | | | |
| 15mm | code39(10mil,6bytes) | 260mm | | | | | | | | | | | | | | | | | | |
| 40mm | code39(15.6mil,6bytes) | 350mm | | | | | | | | | | | | | | | | | | |
| 15mm | code128(10mil,6bytes) | 270mm | | | | | | | | | | | | | | | | | | |
| 20mm | code128(15.6mil,6bytes) | 330mm | | | | | | | | | | | | | | | | | | |
| 30mm | EAN13(15.6mil,13bytes) | 360mm | | | | | | | | | | | | | | | | | | |
| Wireless Transmitting Distance (Without barrier) | 15 - 20M | | | | | | | | | | | | | | | | | | | |
| Infrared induction disrance | — | | | | | | | | | | | | | | | | | | | |
| Optical Source | 650nm Visible red light diode | | | | | | | | | | | | | | | | | | | |
| Reading Precision | ≥ 4mil | | | | | | | | | | | | | | | | | | | |
| Minimum Contrast | ≥ 30% | | | | | | | | | | | | | | | | | | | |
| Decoding Capacity | UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. | | | | | | | | | | | | | | | | | | | |
| Decoding Speed | 100time/second | | | | | | | | | | | | | | | | | | | |
| Barcode Sensitivity | Tilt | ±65° | | | | | | | | | | | | | | | | | | |
| | Totate | ±42° | | | | | | | | | | | | | | | | | | |
| | Deflection | ±60° | | | | | | | | | | | | | | | | | | |
| Data interface | RJ-45 | | | | | | | | | | | | | | | | | | | |
| Mechanical and Electric Performance | | | | | | | | | | | | | | | | | | | | |
| Size(Length x Width x Height) | 92.5×70×154.6 mm | | | | | | | | | | | | | | | | | | | |
| Weight | 168g | | | | | | | | | | | | | | | | | | | |
| Indicator | Siren and LED light | | | | | | | | | | | | | | | | | | | |
| Battery Capacity | 600mah | | | | | | | | | | | | | | | | | | | |
| Max. Power | 350mw | | | | | | | | | | | | | | | | | | | |
| Working Voltage | DC5V | | | | | | | | | | | | | | | | | | | |
| Current | Max.Current | 70ma | | | | | | | | | | | | | | | | | | |
| | Working Current | 66ma | | | | | | | | | | | | | | | | | | |
| | Standby Current | 45ma | | | | | | | | | | | | | | | | | | |
| | Sleeping Current | ≤ 2ua | | | | | | | | | | | | | | | | | | |
| Charging Current | 450ma | | | | | | | | | | | | | | | | | | | |
| Accessory List | | | | | | | | | | | | | | | | | | | | |
| Data Cable | Micro USB | | | | | | | | | | | | | | | | | | | |
| Wireless Receiver | — | | | | | | | | | | | | | | | | | | | |
| CD | 1 | | | | | | | | | | | | | | | | | | | |
| Operation Manual | 1 | | | | | | | | | | | | | | | | | | | |
| Charge station | — | | | | | | | | | | | | | | | | | | | |
| Environmental Parameter | | | | | | | | | | | | | | | | | | | | |
| Storage Temperature | -40°C ~ 60°C | | | | | | | | | | | | | | | | | | | |
| Working Temperature | 0°C ~ 50°C | | | | | | | | | | | | | | | | | | | |
| Relative Humidity | 0 ~ 95% | | | | | | | | | | | | | | | | | | | |
| Height Range | 1.5M | | | | | | | | | | | | | | | | | | | |
| IP Rating | IP52 | | | | | | | | | | | | | | | | | | | |
| Certification | | | | | | | | | | | | | | | | | | | | |
| CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004 | | | | | | | | | | | | | | | | | | | | |

INGER CERTIFICATION ASSESSMENT SERVICES



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05
This is to certify the quality management systems of


Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

Scope of approval
R&D, Production of Barcode Scanning Identification Equipment

Signed by:  Approval Date: 26 Dec. 2014
Expiry Date: 25 Dec. 2017

Shenzhen Yumite Certification Assessment Services Co., Ltd.


China England Accreditation Services Ltd No. 1208

Tel: +86 755 26121760

Fax: +86 755 26121761

Web: www.yumite.com

Add: Room 601, Jiaoling Mansion, 1208 West Chongqing Rd., Futian District, Shenzhen, China, 518037



The certificate information can be checked on the CAS website: WWW.CAS.CN/CN. The validation of the certificate also can be obtained through www.yumite.com or by calling CAS Client Services Dept. This certificate is only valid when used together with related permits unless appropriate. This certificate holder must successfully pass yearly periodical audits to maintain the validity of the certificate after the certificate approval date. The certificate retains the property of CAS, so when it must be returned if the management systems of the certificate holder is approved not to be in conformity with the certificate standard.

INGER CERTIFICATION ASSESSMENT SERVICES



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 E1 0796 R05
This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval
The Related Environmental Management Activities of R&D, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

Signed by:  Approval Date: 26 Dec. 2014
Expiry Date: 25 Dec. 2017

Shenzhen Yumite Certification Assessment Services Co., Ltd.

China England Accreditation Services Ltd No. 1208

Tel: +86 755 26121760

Fax: +86 755 26121761

Web: www.yumite.com

Add: Room 601, Jiaoling Mansion, 1208 West Chongqing Rd., Futian District, Shenzhen, China, 518037



The certificate information can be checked on the CAS website: WWW.CAS.CN/CN. The validation of the certificate also can be obtained through www.yumite.com or by calling CAS Client Services Dept. This certificate is only valid when used together with related permits unless appropriate. This certificate holder must successfully pass yearly periodical audits to maintain the validity of the certificate after the certificate approval date. The certificate retains the property of CAS, so when it must be returned if the management systems of the certificate holder is approved not to be in conformity with the certificate standard.



Certificate of Compliance

Certificate Number: UN2014122403RC-3

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner

Trade Name : Yumite

M/N : YT-1000, YT-760, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-
M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council
RoHS Directive 2011/95/EU. It is only valid in connection with the test report number:
UN2014122403RR-3.

2014-12-24

Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongshuang Industrial Park,
Nanshan District, Shenzhen, P.R.C. 518055
Tel: +86-755-88130096 Fax: +86-755-88180138
<http://www.unt.com.cn> E-mail: info@unt.com.cn



RoHS



EC-R&TTE Certificate

Certificate Number: UN2014122403REC-1

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner

Trade Name : Yumite

M/N : YT-1300, YT-860, YT-1200, YT-1400, YT-1600, YT-2200, YT-2300, YT-2400,
YT-2500, YT-XXXX

| Essential requirement | Applied Specifications/Standards | Documentary Evidence | Result |
|-----------------------|----------------------------------|----------------------|--------|
| Art.3.1(a) Health | Not assessed | | |
| Art.3.1(a) Safety | EN60950-1 | UN2014122403ER-1 | Pass |
| Art.3.1(b) EMC | ETSI EN301 489-1/3 | UN2014122403ER-1 | Pass |
| Art.3.2 Radio | ETSI EN300 440 | UN2014122403ER-2 | Pass |

The EUT described above has been tested by us with the listed standards and found in compliance
with the council R&TTE directive 99/5/EC. It is possible to use CE marking to demonstrate the
compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24

Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongshuang Industrial Park,
Nanshan District, Shenzhen, P.R.C. 518055
Tel: +86-755-88130096 Fax: +86-755-88180138
<http://www.unt.com.cn> E-mail: info@unt.com.cn



CE



Our factory

Yumite

