Description

□□□□□□□□ □□□□□□□ □□□□□□□□ □□□□□□□ □□□□.
□□□□□□□ □□□□□□ □□□□□□ □□□□□□.
□□□□□ □□□□ □□□□□□ □□□□□□□ □□□□ □□□□□□□ □□□□ □□□□□.
□□□□ □□□□□ □□□□□□ □□□□ □□ □□□ □□□□□ □□□ □□□□□□□□□□.
□□□□□ □□ □□□□□□ □□□□□ □□□□□□ □□□□□□□ □□□ □□ □□□□□□ □□□□□□□.
□□□□□□□ □□□□□□ □□□□□□□ □□ □□□□□□□ □□□□□ □□ □□□□□□□□□□ □□□□□□□.

Specification

Para / Model		YT-760A
Image		
Image		
Performance Parameter		
Depth Filed		
Wireless Transmitting Distance (without barrier)		——
Infrared induction Distance		150 - 200mm
Optical Source		650nm Visible red light diode
Reading Percision		≥4mil
Minimum Contrast		≥ 30%
Decoding Capacity		UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.
Decoding Speed		100times/second
Barcode Sensitivity	Tilt	±65°
	Rotate	±42°
	Deflection	±60°
Data Interface		RJ-45
Mechanical and Electric Parameter		
Size(Length x Width x Height)		92.5×70×154.6 mm
Weight		148g
Indicator		Siren and LED light
Battery Capacity		——
Max.Power		500mw
Working Voltage		DC5V
Current	Max.Current	100ma
	Working Current	97ma
	Standby Curent	77ma
	Sleeping Current	——
Charging Current		450ma
Accessory List		
Data Cable		Mirco USB
		——
Wireless Receiver		——
CD		——
Operation Manual		1
Charge Station		——
Holder		1Set
Environmental Parameter		
Storage Temperature		-40°C ~ 60°C
Working Temperature		0°C ~ 50°C
Relative Humidity		0 ~ 95%
Heigth Range		1.5M
IP Rating		IP52
Certification		
CE,RoHS,EMC,LVD，ISO9001:2008,ISO14001:2004		

Application