خفيفة الوزن الجديد ورخيصة ليزر محمول الباركود الماسح الضوئي، YT-760L

Yumite





Description

Yumite

Specification



| | | 1 00000 | | |
|---|--|---|--|--|
| lmage | | Image | | |
| | | Parformance Parameter | | |
| | N. | Performance Parameter | | |
| Depth Filed | | 20mm | | |
| Wireless Tran (without barrie | smitting Distance r) | | | |
| Infrared Induct | tion Distance | * _* * | | |
| Optical Source | W | 650nm Visible red light diode | | |
| Reading Percision | | ≥4mil | | |
| Minimun Contrast Decoding Capacity | | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. | | |
| | ed | 100times/second | | |
| Decoding Spe | T114 | | | |
| | Tilt | ±65° | | |
| Barcode | Rotate | ±65° ±42° | | |
| Barcode Sensitivity | | ±65° | | |
| Barcode Sensitivity | Rotate | ±65° ±42° ±60° | | |
| Barcode Sensitivity Data Cable Size(Length x | Rotate | ±65° ±42° ±60° RJ-45 | | |
| Barcode Sensitivity Data Cable Size(Length x Weight | Rotate Deflection | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator | Rotate Deflection Width x Height) | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac | Rotate Deflection Width x Height) | #65° #42° #60° RJ-45 Mechanical and Electric Parameter 156×64×91 mm 108g Siren and LED light —— | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac | Rotate Deflection Width x Height) | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac | Rotate Deflection Width x Height) | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta | Rotate Deflection Width x Height) | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current | #65° #42° #60° RJ-45 Mechanical and Electric Parameter 156×64×91 mm 108g Siren and LED light 450mw DC5V 90ma 62ma 71ma | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current | #65° #42° #60° RJ-45 Mechanical and Electric Parameter 156×64×91 mm 108g Siren and LED light —— 450mw DC5V 90ma 62ma 71ma —— 450ma | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current | #65° #42° #60° RJ-45 Mechanical and Electric Parameter 156×64×91 mm 108g Siren and LED light 450mw DC5V 90ma 62ma 71ma | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre | Rotate Deflection Width x Height) ge Max.Current Working Current Standby Current Sleeping Current ent | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Station | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent eiver | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent eiver | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp | Rotate Deflection Width x Height) ity qe Max.Current Working Current Standby Current Steeping Current ent erature erature berature | #65° | | |
| Barcode Sensitivity Data Cable Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging curre Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent erature berature dity | #65° | | |
| Weight Indicator Battery Capac Max.Power Working Volta | Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping Current ent erature berature dity | #65° #42° #60° RJ-45 Mechanical and Electric Parameter 156×64×91 mm 108g Siren and LED light 450mw DC5V 90ma 62ma 71ma 450ma Accessory List Micro USB 1 Environmental Parameter 40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% | | |



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6£ Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:







Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsieng Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bac'an District, Sherathen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-41200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.





Sherzhen United Testing Technology Co., Ltd. Room 177-319, Block 1, University Tree Technology Park. 57-20m. South Rection, Fronty Tree Technology Park. Namelson Destrict. Breaches. PRC 315095 164-40-753-86 https://doi.org/10.1516/10.1516/ 164-40-753-86 https://doi.org/10.1516/









EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Y1-1300, YT-850, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

| Essential requirement | | Applied Specifications/Standards | Documentary Evidence | Result |
|-----------------------|--------|----------------------------------|----------------------|--------|
| Art.3.1(a) | Health | Not assessed | | |
| Art 3.1(a) | Safety | EN60950-1 | UNI20141224035R-1 | Pass |
| Art.3.1(b) | EMC | ETSI EN301 489-1/-3 | UNI2014122403ER-1 | Pass |
| Att.3.2 | Radio | ETSI EN300 440 | UNI2014122403ER-2 | Pass |

with the council #ATTE directive 90/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

Date of issue



Shenzhen United Testing Technology Co., Ltd.
Roses 317-319. Block 1. University Toes Technology Park.
97-20ne, Social Section, Hongranising Industrial Park.
Nasionan Darest Shenzhen, PRC 518091
106 - 987-556-660000 Fax-6156-66160118
106 University Section Section Section Section Sec





Our factory



