

Description

Yumite

مصغرة ليزر الباركود محرك المسح الضوئي / ليزر محرك المسح الضوئي / ماسح الباركود وحدة غير Yumite 1D مصغرة ليزر الباركود متكاملة في سوبر ماركت، وتجارة التجزئة / سلسلة محلات scanner.Easily واحد من نموذجي الصين / الباركود متكاملة في سوبر ماركت، وتجارة التجزئة / سلسلة محلات scanner.Easily على kios

نظام مع بأسعار تنافسية.

Feature



USB. و RJ45 دعم inetrface ليزر جهاز استشعار الصورة ومختلف اتصال atimes / دعم chimes التشفير، و USB. مثالية للتطبيقات. chloiceثانية سرعة فك التشفير، و USB-times مثالية للتطبيقات. و USB-USB و USB-USB اثنين من الكابلات الروبوت / اي فون / اللوحي أو جهاز الكمبيوتر دون PC لاستخدامه مع USB-USB و اللوحي أو جهاز الكمبيوتر دون PC الفواص الغواص الفواص

الاستخدامالتوصيل والتشغيل وسهولة الاستخدام لمتوسط.

Specification



	Model	YT-M200	
		Image	
lmage			
Depth Filed		Performance Parameter 20mm 15mm 40mm 15mm 20mm 20mm 15mm 20mm 15mm 20mm 15mm 20mm 15mm 20mm 15mm 20mm 20mm 20mm 30mn 400 300 300 300 300	
Wireless Tran (without barrie	nsmitting Distance	1 <u>1.11.1</u> 1	
Infrared induction Distance		150 - 200mm	
a.cu illuut.		650nm Visible red light diode	
	e	650nm Visible red light diode	
Optical Source		650nm Visible red light diode ≥4mil	
Optical Source Reading Perci Minimum Conf	ision		
Optical Source Reading Perci Minimum Conf Decoding	ision trast	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal	
ptical Source eading Perci linimum Conf ecoding	ision trast eed Tilt	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65°	
ptical Source eading Perci linimum Conf ecoding ecoding Spe arcode	ision trast eed Tilt Rotate	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42°	
ptical Source leading Perci linimum Conf lecoding lecoding Spe larcode lensitivity	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60°	
ptical Source eading Perci linimum Conf ecoding ecoding Spe arcode ensitivity	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Neight	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Bensitivity Data Interface Size(Length x Weight Indicator	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Weight Indicator Battery Capac Max.Power	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Bensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma	
Detical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre	eed Trilt Rotate Deflection Width x Height) city ent Max.Current Working Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— —— —— —— —— —— —— —— —— —— —— —— ——	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Veight Indicator Battery Capac Max.Power	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma	
ptical Source eading Perci linimum Conf lecoding lecoding Spe arcode ensitivity ata Interface lize(Length x /eight ldicator attery Capac lax.Power /orking Current	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma ——	
ptical Source leading Perci linimum Conf lecoding lecoding Speciarcode lensitivity lata Interface lize(Length x leight lodicator lattery Capace lax.Power lovering Current	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capace Max.Power Working Current Charging Curre	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— —— —— —— ——— ————————————————————	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Data Cable	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current rent	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Current Data Cable Wireless Rece	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current rent	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— —— —— —— ——— ————————————————————	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Current Data Cable Wireless Rece CD	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current rent	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List USB—OTG Micro USB —— —— —— —— —— —— —— —— ——— —————————	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curr Data Cable Wireless Rece CD Operation Mai	eed Tritt Rotate Deflection Width x Height) with x Height and the second and th	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— —— —— —— ——— ————————————————————	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curre Data Cable Wireless Rece CD Operation Mai	eed Tritt Rotate Deflection Width x Height) with x Height and the second and th	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——— mw DC5V 95ma 93ma 47ma ——— 450ma Accessory List USB—OTG Micro USB ——— 1 ——— 1 —————————————————————————	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curr Data Cable Wireless Rece CD Operation Mai Charge Station	eed Trilt Rotate Deflection Width x Height) Eity Ent Max.Current Working Current Standby Current Standby Current Steeping Current rent Eiver	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——— mw DC5V 95ma 93ma 47ma ——— 450ma Accessory List USB-OTG Micro USB ——— Environmental Parameter	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Current Charging Curre Operation Mai Charge Station Storage Temp	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Standby Current rent eiver	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——— mw DC5V 95ma 93ma 47ma ——— 450ma Accessory List USB—OTG Micro USB ——— 1 ——— 1 —————————————————————————	
Optical Source Reading Perci Minimum Cont Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Standby Current rent eiver nual n perature perature	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5, Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List USB-OTG Micro USB —— Environmental Parameter -40°C ~ 60°C	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curre C	eed Trilt Rotate Deflection Width x Height) Eity Ent Max.Current Working Current Standby Current Steeping Current rent Eeiver In a contract of the contra	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List USB—OTG Micro USB —— 1 —— Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Current Charging Curre Charging Cur	eed Trilt Rotate Deflection Width x Height) Eity Ent Max.Current Working Current Standby Current Steeping Current rent Eeiver In a contract of the contra	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second	



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6£ Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:







Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsieng Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bac'an District, Sherathen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-41200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.





Sherzhen United Testing Technology Co., Ltd. Room 177-319, Block 1, University Tree Technology Park. 57-20m. South Rection, Fronty Tree Technology Park. Namelson Destrict. Breaches. PRC 315095 164-40-753-86 https://doi.org/10.1516/10.1516/ 164-40-753-86 https://doi.org/10.1516/









EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Y1-1300, YT-850, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art 3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
Att.3.2	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

with the council #ATTE directive 90/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

Date of issue



Shenzhen United Testing Technology Co., Ltd.
Roses 317-319. Block 1. University Toes Technology Park.
97-20ne, Social Section, Hongranising Industrial Park.
Nasionan Darest Shenzhen, PRC 518091
106 - 987-556-660000 Fax-6156-66160118
106 University Section Section Section Section Sec





Our factory



