بلوتوث اللاسلكية ماسح الباركود الليزر USB

الماسح الضوئي الباركود الليزر بلوتوث من السهل للاستخدام. ويمكن إرفاقها مع الجهاز الذي هو مع بلوتوث، لا أكثر دائرة الرقابة الداخلية الدعم، ماك، الروبوت، والهواتف الذكية، ونقاط البيع وهلم جرا software.YT-890.

Para / Model		YT-890
Image		
Image		
Performance Parameter		
Depth Filed		
Wireless Transmitting Distance (Without barrier)		15 - 20M
Infrared induction disrance		——
Optical Source		650nm Visible red light diode
Reading Precision		≥ 4mil
Minimum Contrast		≥ 30%
Decoding Capacity		UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.
Decoding Speed		100time/second
Barcode Sensitivity	Tilt	±65°
	Totate	±42°
	Deflection	±60°
Data interface		RJ-45
Mechanical and Electric Performance		
Size(Length x Width x Height)		92.5×70×154.6 mm
Weight		168g
Indicator		Siren and LED light
Battery Capacity		600mah
Max. Power		350mw
Working Voltage		DC5V
Current	Max.Current	70ma
	Working Current	66ma
	Standby Current	45ma
	Sleeping Current	≤ 2ua
Charging Current		450ma
Accessory List		
Data Cable		Micro USB
		——
Wireless Receiver		1
CD		1
Operation Manual		1
Charge station		——
Environmental Parameter		
Storage Temperature		-40°C ~ 60°C
Working Temperature		0°C ~ 50°C
Relative Humidity		0 ~ 95%
Height Range		1.5M
IP Rating		IP52
Certification		
CE,RoHS,EMC,LVD，ISO9001:2008,ISO14001:2004		