

بلوتوث اللاسلكية ماسح الباركود الليزر USB



الماسح الضوئي الباركود الليزر بلوتوث من السهل للاستخدام. ويمكن إرفاقها مع الجهاز الذي هو مع بلوتوث، لا أكثر دائرة الرقابة الداخلية الدعم، ماك، الروبوت، والهواتف الذكية، ونقاط البيع وهلم جرا software.YT-890.

Para	Model	YT-890
Image		
Image		
Performance Parameter		
Depth Filed		
Wireless Transmitting Distance (Without barrier)	15 - 20M	
Infrared induction disrance	—	
Optical Source	650nm Visible red light diode	
Reading Precision	≥ 4mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.	
Decoding Speed	100time/second	
Barcode Sensitivity	Tilt	±65°
	Totate	±42°
	Deflection	±60°
Data interface	RJ-45	
Mechanical and Electric Performance		
Size(Length x Width x Height)	92.5×70×154.6 mm	
Weight	168g	
Indicator	Siren and LED light	
Battery Capacity	600mah	
Max. Power	350mw	
Working Voltage	DC5V	
Current	Max.Current	70ma
	Working Current	66ma
	Standby Current	45ma
	Sleeping Current	≤ 2ua
Charging Current	450ma	
Accessory List		
Data Cable	Micro USB	
Wireless Receiver	—	
CD	1	
Operation Manual	1	
Charge station	—	
Environmental Parameter		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Height Range	1.5M	
IP Rating	IP52	
Certification		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		

