

3 2014 10 10 10:00:00 10:00:00 10:00:00 d 10:00:00/10:00:00 10:00:00 10:00:00 10:00:00
760- 10 10:00:00 10:00:00 10:00:00L 10:00:00

10:00:00
10:00:00 10:00:00
10:00:00 10:00:00

10:00:00 10 10:00:00 10:00:00 10:00:00 .10:00:00 10:00:00 10 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00
.10:00:00 10:00:00
2.4 10:00:00 10:00:00 10:00:00/10:00:00 :10:00G 10:00:00 10:00:00 10:00:00 10:00:00
10:00:00 10:00:00 10:00:00 433/10:00:00 10:00:00 10:00:00 10:00:00 10:00:00/10:00:00 10:00:00
2 10:00:00 10:00:00D .10:00:00 10:00:00 10:00:00

10:00:00 10 10:00:00 20 10:00:00 10:00:00 10:00:00 10:00:00 10 10 10:00:00 10:00:00 10:00:00 10:00:00 7 10:00:00
10:00:00 10:00:00 10:00:00 10 10 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 .10:00:00 10:00:00 10:00:00 10:00:00 10 10:00:00
.10:00:00 10 10 10:00:00 10 10:00:00 10:00:00 10:00:00

!10:00:00 10:00:00 10:00:00 10:00:00 10 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00

10:00:00 10:00:00 Distanc (— — (10:00:00 10:00:00
— - 10:00:00 10:00:00 10:00:00 10:00:00
650nm 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00
4 ≤ 10:00:00 10:00:00mil
%30 ≤ 10:00:00 10 10:00:00 10:00:00
10:00:00 10:00:00 10:00:00 " 10:00:00 10:00:00/EAN/10:00:00 10:00:00 10:00:00 10:00:00/EAN 10
10:00:00 10:00:00
10:00:00/EAN128 10:00:00 MSI 10:00:00 Code11 10:00:00 Code39 10:00:00 10:00:00
10:00:00 Code39 10:00:00 Code128 10:00:00 Code128 10:00:00 10:00:00 Codabar 10:00:00 Code93
10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 5 10 10:00:00 2 10:00:00 Codabar 10:00:00 2/5 10 10 2 10:00:00
5 10 2 10:00:00 barcodes " 10:00:00 10:00:00 10:00:00
100 10:00:00 10:00:00times/s
° 65± 10:00:00 10:00:00 10:00:00
° 42± 10:00:00
° 60± 10:00:00
10:00:00 10:00:00 10:00:00 RJ-45
10:00:00 10:00:00 10:00:00 10:00:00
10:00:00) 10:00:00 x 10:00:00 x 10 91 × 64 × 156 (10:00:00
108 10 (10:00:00 10:00:00) 10:00:00
10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 10:00:00
10:00:00 10:00:00 10:00:00 - —
Max.Power 450mw
10:00:00 10:00:00 DC5V
10:00:00 Max.Curren 90ma
62 10:00:00ma 10:00:00
71 10:00:00 10:00:00ma
— - 10:00:00 10:00:00
450 10:00:00ma 10:00:00
10:00:00 10:00:00
10:00:00 10:00:00 10:00:00 10:00:00 10:00:00 line(1.8m)

-- 0000000000 0000
-- 00000000 00000000 0000
0000 1 0000 000000
-- 000 000000
00000000 00000000
00000000 000000 0000 ° 000000 0000 60 ~ 0
000000 0000 50 ~ 000000 0000 0 00000000 0000 0000
%95 ~ 0 00000000 00000000
000 1.5 000000000 0000
00000000 00000000 000000: IP52

000000000:
CE 0 RoHS 0 EMC 0 LVD 0 ISO9001:2008 0 ISO14001:2004







Yumite



Yumite



Yumite

2014-0812
LASER LIGHT
DO NOT STARE INTO BEAM