□□ □□ □□□□□ □□□□□□□□ □□□□□□□ □□□□□□□□ □□□ □□□□□□ □□□□□□ □□□□ □□□□□□ □□□□□□□□ □□□□□□ □□□□□□□-M200

□□□ 200-150 □□□□□ □□□□□□□□ □□□□□□□ □□□ □□□□□□
650nm □□□□□ □□□□ □□□□□□ □□□□□□ □□□□□ □□□□□□ □□□□□□
4≤ □□□□□□ □□□□mil
%30 ≤ □□□□□□□ □□ □□□□□□ □□□□
□□□□□□□□□□□ □□□□□□□□ □□□□□" □□□□□□□□ □□□□□/EAN/□□□□□□□□□□□ □□□□□□□□ □□□□□ □□□□/EAN □□ □□□□□□□□□□□□□□
□□□□□□□/EAN128□ Code39□ MSI□ Code11□ Code39 □□□□□ □□□
□□□□□□□□ Code39□ Code128□ Code128 □□□ □□□□ Codabar□ Code93□
□□□□□□□□□□ □□□□□□□ □□□□□ □□□□□ □□□□□ 5 □□ □□□□□□ 2 □□□□□ Codabar□ □2/5 □5 □□ 2 □□□□□□□
5 □□ 2 □□□□□ barcodes□ " □□□□□□□ □□□□□□ □□□□□□□
100 □□□□ □□times/s
° 65± □□□□□ □□□□□□□□ □□□□□□
° 42± □□□□□
° 60± □□□□□□
□□□□□□ □□□□□ □□□□□□ USB
□□□□□□□□□□□ □□□□□□□□□□□ □□□□
□□□□□) □□□□□ x □□□□□ x □□ 22.4 × 50 × 70.3 (□□□□□□□□
51 □ (□□□□ □□□□□□□□) □□□□□
□□□□□□□ □□□□□□□ □□□□□ □□□□ □□□
Max.Power □□□□□□□
□□□□□ □□□□□ DC5V
□□□□□□ Max.Curren 95ma
93 □□□□□ma □□□□□□
47 □□□□□□□ □□□□□□□□□□ma
450 □□□ma □□□□□□
□□□□□□□□ □□□□□
□□□□□□□□ □□□□□ □□□□□□□□ □□□□□□ □□□□ □□□□□□ line(1.5m)
line(0.8m) □□□□□□□□ USB □□□□□□
Line(1.8m) □□□□□□□□ RS232
1 □□□□ □□□□□Piece
□□□□□□□ □□□□□□□
□□□□□□□ □□□□□ □□□□ º □□□□□ □□□□ 60 ~ □
□□□□□ □□□□ 50 ~ □□□□□ □□□□ 0 □□□□□□□ □□□□ □□□□
%95 ~ 0 □□□□□□□ □□□□□□□
□□□ 1.5 □□□□□□□□ □□□□
IP52 □□□□□□□ □□□□□□□ □□□□□

□□□□□□□□:

CE□ RoHS□ EMC□ LVD□ ISO9001:2008□ ISO14001:2004

CAUTION
LASER LIGHT
* DO NOT STARE INTO
BEAM.
MADE IN CHINA

CAUTION
LASER LIGHT
DO NOT STARE INTO
BEAM
MADE IN CHINA


CAUTION
LASER LIGHT
* DO NOT STARE INTO
BEAM.
MADE IN CHINA


CAUTION
LASER LIGHT
* DO NOT STARE INTO
BEAM.
MADE IN CHINA

Yumite
YT-M200-B
LASER SCANNER
CE ROHS
SERIAL NO
COLOR
Black
Gray
INTERFACE
USB power cords
Laser Barcode Scanner
Operation Manual

CAUTION
LASER LIGHT
DO NOT STARE INTO
BEAM