```
480 \times 752
280-0 40 39 0 0 0 0 0 mm(10mil)85 mm~325mm(15mil)
PDF417 60 225-\( \propto \text{mm}(10\text{mil})60 \\ \propto \text{mm} \( \propto 340\text{mm}(15\text{mil}) \)
155-00 20 0000000 00000mm(10mil)35 0mm~235mm(15mil)
______ (ECC200] ECC000] 050, 080, 100,140). "
300 □□□□ □□times/s
° 55± 00000 0000000 000000
° 360± □□□□□
° 55± 00000
NOTICE THE RESULT OF THE PROPERTY OF THE PROPE
1 00000 000 000 0000 00000.Auto 2.RS232 000000/0000000 00000 .3 000000
00000 00000 00000 00000 00000 00000 00000
\Pi 47 \Pi\Pi\Pi
Max.Power 1150mw
□□□□□ Max.Curren 230ma
50 000000 00000000ma
\Pi\Pi \Pi\Pi\Pi\Pi\Pi\Pi RS232(1.8M)
cable(1.2m) \square \square 2.54 \square \square \square \square
%95 ~ 0 <u>______</u>
IP52 000000 000000 00000
```

CE $\sqcap$  RoHS $\sqcap$  EMC $\sqcap$  LVD $\sqcap$  ISO9001:2008 $\sqcap$  ISO14001:2004