

ماك / الروبوت لاسلكي جهاز ليزر بلوتوث ماسح / IOS ربط
الباركود الصينية لصناعة المورد

Yumite



Para	Model	YT-890
Image		
Image		
Performance Parameter		
Depth Filed		
Wireless Transmitting Distance (Without barrier)	15 - 20M	
Infrared induction disrance	—	
Optical Source	650nm Visible red light diode	
Reading Precision	≥ 4mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.	
Decoding Speed	100time/second	
Barcode Sensitivity	Tilt	±65°
	Totate	±42°
	Deflection	±60°
Data interface	RJ-45	
Mechanical and Electric Performance		
Size(Length x Width x Height)	92.5×70×154.6 mm	
Weight	168g	
Indicator	Siren and LED light	
Battery Capacity	600mah	
Max. Power	350mw	
Working Voltage	DC5V	
Current	Max.Current	70ma
	Working Current	66ma
	Standby Current	45ma
	Sleeping Current	≤ 2ua
Charging Current	450ma	
Accessory List		
Data Cable	Micro USB	
Wireless Receiver	—	
CD	1	
Operation Manual	1	
Charge station	—	
Environmental Parameter		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Height Range	1.5M	
IP Rating	IP52	
Certification		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		