

الوعرة الماسح الضوئي الباركود المحمول بلوتوث لـAndroid.Windows، موبايل IOSYT-890

Yumite



Description

Yumite

هذا هو الوقت الحقيقي نقل التكنولوجيا بلوتوث البيانات واحدة من أهم الباركود ليزر لاسلكية إبتيرجراتيد بسهولة للروبوت / ويندوز موبايل / دائرة www.china-barcode-scanner.com الماسح الضوئي من الرقابة الداخلية للاستخدام المباشر بدون تثبيت برنامج التشغيل.

Feature

Yumite

1. Bluetotoh ماسح الباركود
2. الروبوت / اي فون المحمول / اللوحي استخدام الكمبيوتر for
3. Rugged. صب
4. موبايل الباركود Bluetooth. ماسحة
5. سائق No
6. PC. الاستخدام المباشر

Para	Model	YT-890																		
Image																				
Image																				
Performance Parameter																				
Depth Filed	<table border="1"> <tr> <td>20mm</td> <td>EAN13(10mil,13bytes)</td> <td>250mm</td> </tr> <tr> <td>15mm</td> <td>code39(10mil,6bytes)</td> <td>260mm</td> </tr> <tr> <td>40mm</td> <td>code39(15.6mil,6bytes)</td> <td>350mm</td> </tr> <tr> <td>15mm</td> <td>code128(10mil,6bytes)</td> <td>270mm</td> </tr> <tr> <td>20mm</td> <td>code128(15.6mil,6bytes)</td> <td>330mm</td> </tr> <tr> <td>30mm</td> <td>EAN13(15.6mil,13bytes)</td> <td>360mm</td> </tr> </table>		20mm	EAN13(10mil,13bytes)	250mm	15mm	code39(10mil,6bytes)	260mm	40mm	code39(15.6mil,6bytes)	350mm	15mm	code128(10mil,6bytes)	270mm	20mm	code128(15.6mil,6bytes)	330mm	30mm	EAN13(15.6mil,13bytes)	360mm
20mm	EAN13(10mil,13bytes)	250mm																		
15mm	code39(10mil,6bytes)	260mm																		
40mm	code39(15.6mil,6bytes)	350mm																		
15mm	code128(10mil,6bytes)	270mm																		
20mm	code128(15.6mil,6bytes)	330mm																		
30mm	EAN13(15.6mil,13bytes)	360mm																		
Wireless Transmitting Distance (Without barrier)	15 - 20M																			
Infrared induction distance	—																			
Optical Source	650nm Visible red light diode																			
Reading Precision	≥ 4mil																			
Minimum Contrast	≥ 30%																			
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.																			
Decoding Speed	100time/second																			
Barcode Sensitivity	Tilt	±65°																		
	Totate	±42°																		
	Deflection	±60°																		
Data interface	RJ-45																			
Mechanical and Electric Performance																				
Size(Length x Width x Height)	92.5×70×154.6 mm																			
Weight	168g																			
Indicator	Siren and LED light																			
Battery Capacity	600mah																			
Max. Power	350mw																			
Working Voltage	DC5V																			
Current	Max.Current	70ma																		
	Working Current	66ma																		
	Standby Current	45ma																		
	Sleeping Current	≤ 2ua																		
Charging Current	450ma																			
Accessory List																				
Data Cable	Micro USB																			
Wireless Receiver	—																			
CD	1																			
Operation Manual	1																			
Charge station	—																			
Environmental Parameter																				
Storage Temperature	-40°C ~ 60°C																			
Working Temperature	0°C ~ 50°C																			
Relative Humidity	0 ~ 95%																			
Height Range	1.5M																			
IP Rating	IP52																			
Certification																				
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004																				

Our factory

Yumite



Application

Yumite

