

**USB / السلكية الليزر صناعة السيارات في معنى مع حامل و
كابل وعرة قذيفة المورد في الصين RS232**



Para	Model	YT-760A
Image		
Image		
Performance Parameter		
Depth Filed		
Wireless Transmitting Distance (without barrier)	---	
Infrared induction Distance	150 - 200mm	
Optical Source	650nm Visible red light diode	
Reading Percision	≥4mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.	
Decoding Speed	100times/second	
Barcode Sensitivity	Tilt	±65°
	Rotate	±42°
	Deflection	±60°
Data Interface	RJ-45	
Mechanical and Electric Parameter		
Size(Length x Width x Height)	92.5×70×154.6 mm	
Weight	148g	
Indicator	Siren and LED light	
Battery Capacity	---	
Max.Power	500mw	
Working Voltage	DC5V	
Current	Max.Current	100ma
	Working Current	97ma
	Standby Current	77ma
	Sleeping Current	---
Charging Current	450ma	
Accessory List		
Data Cable	Mirco USB	
Wireless Receiver	---	
CD	---	
Operation Manual	1	
Charge Station	---	
Holder	1Set	
Environmental Parameter		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Heigth Range	1.5M	
IP Rating	IP52	
Certification		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		

