/ USBالسلكية الليزر صناعة السيارات في معنى مع حامل و كابل وعرة قذيفة المورد في الصين RS232



	Model	YT-760A
		Image
lmage		
		Performance Parameter
Depth Filed		20mm EANI3(10mil,13loytes)250mm 15min coole39(10mil,6loytes) 260mm 15min coole39(15.6mil,6bytes) 350mm coole128(10mil,6loytes) 270mm 20min 20min EANI3(15.6mil,6loytes) 330mm EANI3(15.6mil,13loytes) 360mm 0 100 200 300 400
Wireless Transmitting Distance (without barrier)		
Infrared induction Distance		150 - 200mm
Optical Source		650nm Visible red light diode
Reading Percis	sion	≥4mil
	root	
Minimum Conti	Webs	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal
Minimum Conti	acity	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second
Minimum Control Decoding Capa Decoding Spec	acity ed Tilt	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65°
Minimum Control Decoding Capa Decoding Specification	acity ed Tilt Rotate	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second
Minimum Control Decoding Capa Decoding Specifications Barcode Sensitivity	acity ed Tilt	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate Deflection	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x 1) Weight	acity ed Tilt Rotate Deflection	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g
Decoding Capa Decoding Specific Specif	ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm
Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw
Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to the second to the	acity ed Tilt Rotate Deflection Width x Height)	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw
Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma
Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma ——
Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to the second	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Current Data Cable Wireless Rece	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List
Decoding Capa Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB —— —— ——————————————————————————————
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x to the sensitivity Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———
Decoding Capa Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Steeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ————————————————————————————————————
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station	ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Standby Curent ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x Very Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Temper Relative Humic Heigth Range	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———— 1Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5M
Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%

