

## قارئ الباركود ليزر لاسلكية بلوتوث



الماسح الضوئي الباركود الليزر بلوتوث من السهل للاستخدام. ويمكن إرفاقها مع الجهاز الذي هو مع بلوتوث، لا أكثر دائرة الرقابة الداخلية الدعم، ماك، الروبوت، والهواتف الذكية، المساعد الشخصي الرقمي وهلم software.YT-890 جرا.

Para	Model	YT-890
<b>Image</b>		
Image		
<b>Performance Parameter</b>		
Depth Filed		
Wireless Transmitting Distance (Without barrier)	15 - 20M	
Infrared induction disrance	—	
Optical Source	650nm Visible red light diode	
Reading Precision	≥ 4mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.	
Decoding Speed	100time/second	
Barcode Sensitivity	Tilt	±65°
	Totate	±42°
	Deflection	±60°
Data interface	RJ-45	
<b>Mechanical and Electric Performance</b>		
Size(Length x Width x Height)	92.5×70×154.6 mm	
Weight	168g	
Indicator	Siren and LED light	
Battery Capacity	600mah	
Max. Power	350mw	
Working Voltage	DC5V	
Current	Max.Current	70ma
	Working Current	66ma
	Standby Current	45ma
	Sleeping Current	≤ 2ua
Charging Current	450ma	
<b>Accessory List</b>		
Data Cable	Micro USB	
Wireless Receiver	—	
CD	1	
Operation Manual	1	
Charge station	—	
<b>Environmental Parameter</b>		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Height Range	1.5M	
IP Rating	IP52	
<b>Certification</b>		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		

مرحبا بكم في الاتصال معنا.