

USB Automatické Indukční laserový skener čárových kódů s USB kabelem YT-760A



Description

Yumite

Jeden z nejžhavějších prodej Číny laserový snímač čárových kódů Reader.

1. Dratova Barcode Scanner
2. Laser Barcode Scanner
3. Full automatické indukční
4. With držák / držák / stojan / STOLNÍ / USB kabel
5. Supported PS2, RS232 a port rozhraní USB
6. Wireless kontinuální snímání nebo kabelové ruční skenování
7. OEM / ODM vítány

Specification

Yumite

Para	Model	YT-760A																		
Image																				
Image																				
Performance Parameter																				
Depth Filed	 <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>20mm</td> <td>EAN13(10mil,13bytes)</td> <td>250mm</td> </tr> <tr> <td>15mm</td> <td>code39(10mil,6bytes)</td> <td>260mm</td> </tr> <tr> <td>40mm</td> <td>code39(15.6mil,6bytes)</td> <td>350mm</td> </tr> <tr> <td>15mm</td> <td>code128(10mil,6bytes)</td> <td>270mm</td> </tr> <tr> <td>20mm</td> <td>code128(15.6mil,6bytes)</td> <td>330mm</td> </tr> <tr> <td>30mm</td> <td>EAN13(15.6mil,13bytes)</td> <td>360mm</td> </tr> </table>		20mm	EAN13(10mil,13bytes)	250mm	15mm	code39(10mil,6bytes)	260mm	40mm	code39(15.6mil,6bytes)	350mm	15mm	code128(10mil,6bytes)	270mm	20mm	code128(15.6mil,6bytes)	330mm	30mm	EAN13(15.6mil,13bytes)	360mm
20mm	EAN13(10mil,13bytes)	250mm																		
15mm	code39(10mil,6bytes)	260mm																		
40mm	code39(15.6mil,6bytes)	350mm																		
15mm	code128(10mil,6bytes)	270mm																		
20mm	code128(15.6mil,6bytes)	330mm																		
30mm	EAN13(15.6mil,13bytes)	360mm																		
Wireless Transmitting Distance (without barrier)	---																			
Infrared induction Distance	150 - 200mm																			
Optical Source	650nm Visible red light diode																			
Reading Percision	≥4mil																			
Minimum Contrast	≥ 30%																			
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.																			
Decoding Speed	100times/second																			
Barcode Sensitivity	Tilt	±65°																		
	Rotate	±42°																		
	Deflection	±60°																		
Data Interface	RJ-45																			
Mechanical and Electric Parameter																				
Size(Length x Width x Height)	92.5×70×154.6 mm																			
Weight	148g																			
Indicator	Siren and LED light																			
Battery Capacity	---																			
Max.Power	500mw																			
Working Voltage	DC5V																			
Current	Max.Current	100ma																		
	Working Current	97ma																		
	Standby Current	77ma																		
	Sleeping Current	---																		
Charging Current	450ma																			
Accessory List																				
Data Cable	Mirco USB																			
Wireless Receiver	---																			
CD	---																			
Operation Manual	1																			
Charge Station	---																			
Holder	1Set																			
Environmental Parameter																				
Storage Temperature	-40°C ~ 60°C																			
Working Temperature	0°C ~ 50°C																			
Relative Humidity	0 ~ 95%																			
Heigth Range	1.5M																			
IP Rating	IP52																			
Certification																				
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004																				



Certificate of Compliance

Certificate Number: UN2014122403RC-3

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner

Trade Name : Yumite

M/N : YT-1000, YT-760, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Directive 2011/65/EU. It is only valid in connection with the test report number: UN2014122403RR-3.

2014-12-24
Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongguang Industrial Park,
Nanshan District, Shenzhen, P.R.C. 518055
Tel: +86-755-86130096 Fax: +86-755-86130138
<http://www.untst.com.cn> E-mail: info@untst.com.cn



RoHS





EC-R&TTE Certificate

Certificate Number: UN2014122403EC-1

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner

Trade Name : Yumite

M/N : YT-1300, YT-880, YT-1200, YT-1400, YT-1600, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement	Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a) Health	Not assessed		
Art.3.1(a) Safety	EN60950-1	UN2014122403ER-1	Pass
Art.3.1(b) EMC	ETSI EN301 489-1/3	UN2014122403ER-1	Pass
Art.3.2 Radio	ETSI EN300 440	UN2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in compliance with the council R&TTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.
The scope of evaluation relates to the submitted documents only.

2014-12-24
Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongguang Industrial Park,
Nanshan District, Shenzhen, P.R.C. 518055
Tel: +86-755-86130096 Fax: +86-755-86130138
<http://www.untst.com.cn> E-mail: info@untst.com.cn




