

2D-Barcode-Scanner-Modul YT-M401 ist für den Selbstbedienungsterminal und fünf Anpassung der Oberfläche an.

Shenzhen World Reputation Electronics Technology Co.,Ltd

Model	YT-M401-A	YT-M401-B	YT-M401-C	YT-M401-D
Picture			WV -	
IO Trigger	NO	NO	YES	YES
RS232 Trigger	YES	NO	YES	NO
Auto Trigger	YES	YES	NO	NO
Data line	RS232	2.54mm flex cable	RS232& IO control cable	2.54mm flex cable & IO control cable

Eigenschaften

- 1. 1D- und 2D-Barcode lesen
- 2. Kleine Größe können in verschiedenen Geräten builded
- 3. Unterschiedliche Interface Schnittstelle Wählbar: USB, RS232, IO etc
- 4. Hohe Geschwindigkeit: 280 mal / s
- 5. Unterstützung Anpassung
- 6. Auto Sensing-Funktion

Anwendungen

POS, Logistik, Lagerverwaltung, Daten managemnent, Kiosk, Automatisierungstechnik



Infrared induction distance		150 - 200mm	
Optical Source		620nm Visible red light diode	
Imaging Sensor		CMOS(Image)	
Resolution Ratio		752×480	
Image Resolution		≥ 5mil	
1.0	Code 39	40mm -280mm(10mil); 85mm~325mm(15mil)	
Daniiaa Danii	PDF417	60mm -225mm(10mil); 60mm~340mm(15mil)	
Reading Depth	Data Matrix	20mm -155mm(10mil); 35mm~235mm(15mil)	
	QR Code	35mm -150mm(10mil); 20mm~230mm(15mil)	
Minimum Contrast		≥ 30%	
3	2D	PDF417, QR Code(Model 1/2),micro QR Data Matrix(ECC200, ECC000,050, 08 0, 100,140).	
Barcode Types	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, I TF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 1 1, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey etc.	
Decoding Speed		300times/s	
	Tilt	±55°	
Barcode Sensitivit	Rotate	±360°	
У	Deflection	±55°	
Data Interface Port		TTL or R\$232	
three trigger mode		1.Auto-trigger 2.RS232 trigger 3. IO signal trigger	
Mechanical and Ele	ectric Performa	nce	
Size(Length x Width x Height)		70.3×50×22.4 mm	
Weight		47g	
Indicator		Siren and LED light	
Max.Power		1150mw	
Working Voltage		DC5V	

Current	Max.Curren	230ma	
	Working Current	100ma	
	Stand-by Current	50ma	
Accessory Li	st		
Data line		R\$232(1.8M)	
		2.54mm flex cable (1.2m)	
		IO control cable	
Operation Manual		one	
Environmenta	al Parameter		
Storage Temperature		-40°C ~ 60°C	
Working Temperature		-25°C ~ 60°C	
Relative Humidity		0 ~ 95%	
Height Range		2m	
IP Rating		IP52	
Certificates		ti.	
CE,RoHS,EM	C,LVD, ISO9001:2008,	ISO14001:2004	





CERTIFICATES









Factory

CUSTOMER Customer visit



Our customers came to Yumite company to visit and field trips, they are satisfied with our quality and service.





























SERVICE

Professional and patient pre-sale and after-sale service on our products;



COOPERATION

Stable quality and reasonable price for you to gain long term cooperation;



OEM&ODM

OEM & ODM service for quantity orders;



QUALITY

Sample orders welcomed for quality test;



WARRANTY

Minimum warranty of one year for free.



How about the quality of the products?

There are GE/ROHS/FGG/IEG/IP52/MSDS/UN38.2/LVD/ ISO9001/ISO14001 certifications and reports.



What's the payment way?

We accept Paypal, T/T, L/G, Western Union, MoneyGram.



What's the shipping way?

There are DHL, Fedex, TNT, UPS.(We also can ship the goods by your shipping account or other express agent you provided).



How long can I get the products?

Within seven working days.



How about the after-sales service?

Our product are warranted against manufacturing defects in materials for a period of one year and workmanship for a period two years from date of Manufacture uder normal use. Lifetime maintenance for setting use.



