# Bluetooth Laser-Barcode-Scanner Lieferant Unterstützung iOS, Android, Win7, Win8 YT-890



## Description



Die Bluetooth Laser Barcode-Scanner ist einfach zu verwenden. Es kann mit dem Gerät, das mit Bluetooth ist nicht mehr software.YT-890 Unterstützung iOS, Mac, Android, Smartphone, PDA und so weiter kombiniert werden.

## Specification



Performance Parameter    Performance Parameter	Para Model	YT-890
Performance Parameter  Depth Filed  Depth Filed Depth Filed  Depth Filed  Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed De		Image
Depth Filed    Some   EANI30   Interview   EANI30   EANi3	lmage	Kanado Com de de de de la companya del la companya de la companya
Mithout barrier	Depth Filed	20mm EANI3(10mil,13bytes)250mm  15mm
Without barrier	Wireless Transmitting Distance	15 - 20M
Detail Source   Seading Precision   ≥ 4mil	(Without barrier)	1.00.2511
Decoding Precision   2 4mil   2 30%		650pm Visible red light diede
Second content	~ <del>'</del>	
UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39, MSI, Code11,Code39 Full ASCII, Code39 Troptic, Code128, Code128, Full ASCII, Code39, Troptic, Code128, Code128, Full ASCII, Code39, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.    Decoding Speed		
Tilt	Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal
Totate	Decoding Speed	100time/second
Content		
Data interface	Sonethythy	
Mechanical and Electric Performance	Data interface	1,000,000
Veight   168g		Mechanical and Electric Performance
### Size and LED light  ### S	Size(Length x Width x Height)	92.5×70×154.6 mm
Stattery Capacity   Gomah     Max. Power   350mw     Working Voltage   DC5V     Current   Working Current   45ma     Standby Current   450ma     Standby Current   450ma     Charging Current   100ma     Charges Receiver   1     Charges Receiver   1     Charge station   1     Charge station   1     Charge station   1     Charge Temperature   40°C ~ 60°C     Working Temperature   0°C ~ 50°C     Celative Humidity   0 ~ 95%     Height Range   1.5M     P Rating   IP52     Certification   100ma     Certification   IP52     Certification   100ma     Construction   100ma     Const	Weight	168g
Max. Power   350mw	Indicator	Siren and LED light
Max. Current   Max. Current   Toma   Working Current   Standby Current   45ma	Battery Capacity	600mah
Current         70ma           Working Current         66ma           Standby Current         45ma           Sleeping Current         450ma           Charging Current           Accessory List           Micro USB           —           Vireless Receiver         1           CD         1           Operation Manual         1           Charge station         —           Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52	Max. Power	
Working Current   Standby Current   Standby Current   Steeping Curr		
Standby Current         45ma           Sleeping Current         ≤ 2ua           Accessory List           Data Cable         Micro USB           Wireless Receiver         1           CD         1           Operation Manual         1           Charge station         Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52	Working Current	
Accessory List	Standby Current	45ma
Accessory List   Micro USB		
Micro USB	onarging Current	
Vireless Receiver	D-4- C-11-	
CD		Y
Departion Manual	Wireless Receiver	
Charge station         —           Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Vorking Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52           Certification	Operation Manual	
Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52           Certification	Charge station	
Storage Temperature         -40 °C ~ 60 °C           Working Temperature         0 °C ~ 50 °C           Relative Humidity         0 ~ 95 %           Height Range         1.5 M           P Rating         IP52           Certification		
Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Storage Temperature	-40°C ~ 60°C
Height Range 1.5M P Rating IP52 Certification	Working Temperature	
P Rating IP52  Certification		
Certification		1 4 5 5
	IP Rating	
OL,13010,LVD, 1003001.2000,100 14001.2004	IP Rating	IP52



#### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansson, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







### CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6f, Xingqiang Commercial Mansion, No. 1 Dealying Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenshen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Bossen District, Shenzhen

Signed by:











## **Our factory**



Shenzhen Weltruf Electronics Technology Co., Ltd ist ein China Barcode-Scanner Herstellung. Es ist bluetooth Scanner Lieferant China.

