Hohe Qualität verdrahtete CCD Barcode-Scanner



Description

Holen Sie sich überragende optische Leistung mit einer Mindestauflösung und einer maximalen Leseabstand mit diesem Kontakt CCD Barcode-Scanner. Es verfügt über ein robustes und zuverlässiges Design und eine Plug & Play-USB-Schnittstelle. Es ist einfach zu installieren und zu verwenden.



Feature

Die Merkmale und niedrigeren Kosten machen diesen Handheld USB CCD Barcode Scanner die beste Lösung für den Einzelhandel, medizinische und leichte industrielle Anwendungen. Nehmen Sie ein heute!

Die Yumite USB Handheld-Barcode-Scanner-CCD geringeren Kosten liefert einfache, qualitativ hochwertige Scannen für eine breite Palette von Datenerfassungsfunktionen zur Verbesserung der Routinegeschäften automatisiert papierbasierte Prozesse und steigern die Produktivität.

Holen Sie sich überragende optische Leistung mit einer Mindestauflösung und einer maximalen Leseabstand mit diesem Kontakt CCD Barcode-Scanner. Es verfügt über ein robustes und zuverlässiges Design und eine Plug & Play-USB-Schnittstelle. Es ist einfach zu installieren und zu verwenden.

USB Handheld-Barcode-Scanner-CCD geringeren Kosten YT-1001 ist in der Lage, Geschwindigkeit, Genauigkeit und Produktivität zu verbessern.

Die Scan-Engine verfügt über keine beweglichen Teile für jahrelangen zuverlässigen Betrieb Lesen beliebten 1D-Barcodes wie UPC, EAN, ASCII, MSI / PLESSEY, GS1 DataBar und mehr. Einfach zu realisieren und zu handhaben, eine integrierte Tastatur Keil Decoder sendet gescannten Daten an eine aktive Anwendung, wo es scheint, als ob sie manuell eingegeben werden oder direkt in den Computer eingegeben. Seine vielseitige schaltbare USB oder RS232-Kabel Schnittstelle integriert mit den meisten PCs, ohne eine externe Stromversorgung. Mit einer Abtastrate von 280-mal pro Sekunde und eine genaue Lesereichweite von bis zu 50 cm (20 in.), Bietet dieses Modell eine effektive und effiziente, Allzweck täglichen Scan-Lösung für weniger anspruchsvolle Point-of-Sale, Büro und andere geringem Umgebungslicht-Anwendungen, um die manuelle Dateneingabe, Geschwindigkeitsverkehr zu minimieren und Fehler zu reduzieren.



		YT-1001		
Image		Image		
Depth Filed		20mm code39(10mil,6bytes) 310mm 20mm 20mm 20mm 20mm 20mm 20mm 20mm		
Wireless Tran (without barrie	smitting Distance	s s		
Infrared induct		——————————————————————————————————————		
Optical Source		620nm Visible red light diode		
Imaging Sensor		CCD		
Image Resolution		2500Pixel		
Reading Preci		≥ 5mil		
Minimum Conf	ırası	≥ 30%		
	acity	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect.		
Decoding Cap				
Decoding Cap		280times/second		
Decoding Spe Barcode	Tilt	±55°		
Decoding Spe				
Decoding Spe Barcode	Tilt Rotate Deflection	±55° ±25°		
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75°		
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75° RJ-45		
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator	Tilt Rotate Deflection Width x Height)	±55° ±25° ±75° 175° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height)	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height)	±55° ±25° ±75° RJ-45 RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height)	±55° ±25° ±775° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw DC5V		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	Tilt Rotate Deflection Width x Height)	±55° ±25° ±75° RJ-45 RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma ————		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Steeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent eiver	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB RS232 Cable —— 1 —— Environment Parameter -40°C ~ 60°C		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent eiver mual n erature perature	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi	Tilt Rotate Deflection Width x Height) wity ge Max.Current Working Current Standby Current Steeping current ent erature erature dity	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Current Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi Height Range	Tilt Rotate Deflection Width x Height) wity ge Max.Current Working Current Standby Current Steeping current ent erature erature dity	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————		
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi	Tilt Rotate Deflection Width x Height) wity ge Max.Current Working Current Standby Current Steeping current ent erature erature dity	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————		

CERTIFICATE OF REGISTRATION

Certification

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

as been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:





CERTIFICATE OF REGISTRATION

Certificate No. 117 14 €1 0796 R05 This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6f, Ximgqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenshen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Manaion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Bacon District, Shenzhen

Signed by:







Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Sherathen World Reputation Electronics Technology Co., Ltd.

6f. B Building, B Area, Xingqiang Buainess Building, No. 1, Dezheng Road,
Shiong Community, Shiyan, Bacran Datrict, Shenzhen
Sherathen World Reputation Electronics Technology Co., Ltd.

6f. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road,
Shiong Community, Shiyan, Bacran District, Shenzhen
Bar-code Scanner
Vurnitie. Applicant

YUMBB YT-1000, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Directive 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.





RoHS

Date of saue







EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Sherushen World Reputation Electronics Technology Co., Ltd.
6F. 8 Building, 8 Area, Xingqiang Business Building, No. 1, Desheng Road,
Shlong Community, Shiyan, Bao an District, Sherushen
Shenzhen World Regutation Electronicids Technology Co., Ltd.
6F. 8 Building, 8 Area, Xingqiang Business Building, No. 1, Dezheng Road,
Shlong Community, Shiyan, Bao an District, Sherushen
Bar-code Scanner
Vereits Applicant

YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 480-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in complice with the council RATTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24



Date of issue Shenzhen United Testing Technology Co., Ltd.

Room 311-316 Block 1. University Train Technology 5" Zone, South Section, Honghusing Industrial Park, Narichan Detrick, Shendren, PRC \$18050 Ser +98,755-80180900 Fax +96-755-98140118 Industrial Park Park +96-755-98140118







Useage











