# Hot Verkauf USB verdrahtete CCD Handheld-Barcode Reader YT-1001



### Description



Erhalten Sie überlegene optische Leistung mit einer Mindestauflösung und einer maximalen Leseabstand mit diesem Kontakt CCD Barcode-Scanner. Es verfügt über ein robustes und zuverlässiges Design und eine Plug & Play-USB-Schnittstelle. Es ist einfach zu installieren und zu verwenden.

Die Merkmale und geringeren Kosten machen diesen USB-Handheld CCD Barcode Scanner die beste Lösung für den Einzelhandel, medizinischen und leichte industrielle Anwendungen. Heben Sie ein heute.

Die Yumite USB Handheld-CCD Barcode-Scanner-geringeren Kosten liefert grundlegende hochwertige Scannen für ein breite Palette an Datenerfassungsfunktionen zur Verbesserung der Routinegeschäften Automatisierung papierbasierter Prozesse und steigern die Produktivität.

Die Scan-Engine verfügt über keine beweglichen Teile für jahrelangen zuverlässigen Betrieb liest beliebten 1D-Barcodes einschließlich UPC, EAN, ASCII, MSI / PLESSEY, GS1 DataBar und mehr. Einfach zu implementieren und einfach zu bedienen, ein eingebautes Keyboard Wedge Decoder gescannten Daten an ein sendet aktive Anwendung, wo es scheint, als ob es manuell eingegeben oder direkt in den Computer eingegeben. Seine vielseitige schaltbare USB oder RS232-Kabel-Schnittstelle integriert mit den meisten PCs, ohne eine externe Stromversorgung. Mit einer Abtastrate von 280 Mal pro Sekunde und eine genaue

Lesereichweite von bis zu 50 cm (20 in.), Dieses Modell bietet eine effektive und effiziente, Allzweck tägliche Durchforsten Lösung für weniger anspruchsvolle Point-of-Sale, Office und andere geringem Umgebungslicht Anwendungen, um die manuelle Dateneingabe, Geschwindigkeit Transaktionen minimieren und Fehler.

## **Specification**



		The control of the co	
Image  Depth Filed		Performance Parameter    Code 39(10nil,6by tes) 310nin	
Infrared induct		——————————————————————————————————————	
Optical Source		620nm Visible red light diode	
Imaging Sensor		CCD	
Image Resolution		2500Pixel	
Reading Precision  Minimum Contrast		≥ 5mil	
Minimum Contrast		≥ 30%	
Decoding Capacity		Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect.	
Decoding Cap			
Decoding Cap		280times/second	
Decoding Spe Barcode	Tilt	±55°	
Decoding Spe			
Decoding Spe Barcode	Tilt Rotate Deflection	±55° ±25°	
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75°	
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75° RJ-45	
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator	Tilt Rotate Deflection  Width x Height)	±55° ±25° ±75°  175°  RJ-45  Mechanical and Electric Performance 92.5×70×154.6 mm	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection  Width x Height)	#55° #25° #75° #75° RJ-45  Mechanical and Electric Performance 92.5×70×154.6 mm 127g  Siren and LED light ——	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection  Width x Height)	±55° ±25° ±75° RJ-45 RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection  Width x Height)	±55° ±25° ±775° RJ-45  Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw DC5V	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	Tilt Rotate Deflection  Width x Height)	±55° ±25° ±75° RJ-45 RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current	±55° ±25° ±75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  —— 650mw DC5V 130ma	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current	±55° ±25° ±75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  —— 650mw DC5V 130ma 86ma	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current	#55° #25° #75° RJ-45  Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma ————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current	±55° ±25° ±75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  —— 650mw DC5V 130ma 86ma	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45  Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light ——  650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Steeping current ent	#55° #25° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light ——  650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta  Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current ent  eiver	#55° #25° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  —— 650mw DC5V 130ma 86ma 42ma —— Accessory List  Micro USB RS232 Cable —— 1 —— Environment Parameter  -40°C ~ 60°C	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp	Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Current Sleeping current ent  eiver  mual n  erature perature	#55° #25° #75° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi	Tilt Rotate Deflection  Width x Height)  wity  ge Max.Current Working Current Standby Current Steeping current ent  erature erature dity	#55° #25° #75° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Current Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi Height Range	Tilt Rotate Deflection  Width x Height)  wity  ge Max.Current Working Current Standby Current Steeping current ent  erature erature dity	#55° #25° #75° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi	Tilt Rotate Deflection  Width x Height)  wity  ge Max.Current Working Current Standby Current Steeping current ent  erature erature dity	#55° #25° #75° RJ-45  Mechanical and Electric Performance  92.5×70×154.6 mm  127g Siren and LED light  ———————————————————————————————————	



#### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







#### CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6£ Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:







# Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsieng Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-41200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.





Sherzhen United Testing Technology Co., Ltd. Room 177-319, Block 1, University Tree Technology Park. 57-20m. South Rection, Fronty Tree Technology Park. Namelson Destrict. Breaches. PRC 315095 164-40-753-86 https://doi.org/10.1516/10.1516/ 164-40-753-86 https://doi.org/10.1516/









#### **EC-R&TTE** Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Y1-1300, YT-850, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art 3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
Att.3.2	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

with the council #ATTE directive 90/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

Date of issue



Shenzhen United Testing Technology Co., Ltd.
Roses 317-319. Block 1. University Toes Technology Park.
97-20ne, Social Section, Hongranising Industrial Park.
Nasionan Darest Shenzhen, PRC 518091
106 - 987-556-660000 Fax-6156-66160118
106 University Section Section Section Section Sec





**Our factory** 



