

Strong compatibility

Compatible with multiple mobile device such as Android, IOS smart phones and tablets



Linux



Android



Windows



MAC

Product Parameters

Light Source:

630nm Red LED

Scan Mode:

Automatic inductive

Precision:

4mil

Optical System:

640*480pixel

Visual Indicator:

Speaker, LED

Motion Tolerance:

3meter/second

Scan Depth:

0-160mm(EAN 13 13mil, PCS=90%)

Interface:

USB-HID, USB-COM, RS232

Dimension:

97*95*167mm

Weight:

379.5g

Material:

ABS+PC

Drop Resistance:

Withstands multiple 1.5m drops to concrete

Current:

150mA

Cecode Capability:

1D: Code128, UCC/EAN-128, AIM-128, EAN-8, EAN-13, ISSN/ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Codabar, Matrix 2 of 5, Plessey, Interleaved 25, Standard 25, MIS-Plessey, Code 39, Code 93, Code 11, GS1-DataBarTM(RSS)(RSS-14, RSS-Limited, RSS-Expand).
2D: PDF417, Data Matrix, (ECC200, 050, ECC000, 080, 100, 140), QR Code(QR1/2, Micro), Hanxin.

Dual good reading indicator

Double scan code prompt, easy to deal with all kinds of noisy cashier scan code environment



Light Tips



Buzzer Feedback

