




Description

Mini-Barcode-Scanner ist für den mobilen, PC und Selbstbedienungsterminals Verwendung.

Unterstützung Anpassung der Oberfläche an und lesen Sie einfach mehr Wasser / Stromrechnung Barcodes.

Kann integrieren PDA als kleinste Größe 21,3 * 18 * 9,4 mm.

Fallresistenz und können Bildschirm-Barcodes zu lesen.

Para	Model	ER01	CCD Module Barcode Reader																		
Picture																					
Product Picture																					
Performance Parameter																					
Depth Filed	 <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>80mm</td> <td>EAN13(10mil,13bytes)</td> <td>110mm</td> </tr> <tr> <td>80mm</td> <td>code39(10mil,6bytes)</td> <td>110mm</td> </tr> <tr> <td>40mm</td> <td>code128(10mil,6bytes)</td> <td>140mm</td> </tr> <tr> <td>70mm</td> <td>code128(13.33mil,6bytes)</td> <td>100mm</td> </tr> <tr> <td>100mm</td> <td>code128(13mil,6bytes)</td> <td>170mm</td> </tr> <tr> <td></td> <td>50mm EAN13(10mil,13bytes)</td> <td>160mm</td> </tr> </table>			80mm	EAN13(10mil,13bytes)	110mm	80mm	code39(10mil,6bytes)	110mm	40mm	code128(10mil,6bytes)	140mm	70mm	code128(13.33mil,6bytes)	100mm	100mm	code128(13mil,6bytes)	170mm		50mm EAN13(10mil,13bytes)	160mm
80mm	EAN13(10mil,13bytes)	110mm																			
80mm	code39(10mil,6bytes)	110mm																			
40mm	code128(10mil,6bytes)	140mm																			
70mm	code128(13.33mil,6bytes)	100mm																			
100mm	code128(13mil,6bytes)	170mm																			
	50mm EAN13(10mil,13bytes)	160mm																			
Optical Source	620nm Visible red light diode																				
Imaging Sensor	CCD																				
Resolution Ratio	2500 pixel																				
Image Resolution	≥ 5mil																				
Minimum Contrast	≥ 30%																				
Barcode Types	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar etc.																				
Decoding Speed	280times/s																				
Barcode Sensitivity	Tilt	±55°																			
	Rotate	±25°																			
	Deflection	±75°																			
Data Interface Port	FPC flat cable、 separation distance: 12*0.5mm																				
Mechanical and Electric Performance																					
Size(Length x Width x Height)	21.3*18*9.4mm																				
Weight (except cable)	3g																				
Indicator	buzzer and LED light																				
Max.Power	400mw																				
Working Voltage	DC5V																				
Current	Max.Current	102ma																			
	Working Current	62ma																			
	Stand-by Current	20ma																			
	Sleeping Current	—																			
Accessory List																					
Data line	RS232 data line																				
Environmental Parameter																					
Storage Temperature	-40°C ~ 60°C																				
Working Temperature	0°C ~ 50°C																				
Relative Humidity	0 ~ 95%																				
Certificates																					
CE,RoHS,EMC,LVD, ISO9001:2008, ISO14001:2004																					
**Test condition: Code 39, 3 Bytes ; The minimum of barcode width = 10mil; width to narrow ratio = 2.5:1 ; barcode height = 40mm; Test Distance = 180mm;Environment Temperature=25°C ; Environment Illumination= 200 LUX																					





Certificate of Compliance

Certificate Number: UN2014122403RC-3

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner
Trade Name : Yumite
M/N : YT-1000, YT-760, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321-3:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Directive 2011/65/EU. It is only valid in connection with the test report number: UN2014122403RR-3.

2014-12-24
Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongguang Industrial Park,
Nanshan District, Shenzhen, PRC. 518055
Tel: +86-755-86180096 Fax: +86-755-86180156
http://www.uni-test.com Email: info@uni-test.com



RoHS





EC-R&TTE Certificate

Certificate Number: UN2014122403EC-1

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner
Trade Name : Yumite
M/N : YT-1300, YT-480, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-3400, YT-2500, YT-XXXX

Essential requirement	Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a) Health	Not assessed		
Art.3.1(a) Safety	EN60950-1	UN2014122403SR-1	Pass
Art.3.1(b) EMC	ETSI EN301 488-1/3	UN2014122403ER-1	Pass
Art.3.2 Radio	ETSI EN300 440	UN2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in compliance with the council R&TTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.
The scope of evaluation relates to the submitted documents only.

2014-12-24
Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongguang Industrial Park,
Nanshan District, Shenzhen, PRC. 518055
Tel: +86-755-86180096 Fax: +86-755-86180156
http://www.uni-test.com Email: info@uni-test.com

