

# USB Bluetooth Laser Barcode-Scanner



Die Bluetooth Laser Barcode-Scanner ist einfach zu verwenden. Es kann mit dem Gerät, das mit bluetooth, nicht mehr software.YT-890 Unterstützung iOS, Mac, Android, Smartphone, POS-Terminal und so weiter ist gepaart werden.

Para	Model	YT-890																		
<b>Image</b>																				
Image																				
<b>Performance Parameter</b>																				
Depth Filed	<table border="1"> <tr> <td>20mm</td> <td>EAN13(10mil,13bytes)</td> <td>250mm</td> </tr> <tr> <td>15mm</td> <td>code39(10mil,6bytes)</td> <td>260mm</td> </tr> <tr> <td>40mm</td> <td>code39(15.6mil,6bytes)</td> <td>350mm</td> </tr> <tr> <td>15mm</td> <td>code128(10mil,6bytes)</td> <td>270mm</td> </tr> <tr> <td>20mm</td> <td>code128(15.6mil,6bytes)</td> <td>330mm</td> </tr> <tr> <td>30mm</td> <td>EAN13(15.6mil,13bytes)</td> <td>360mm</td> </tr> </table>		20mm	EAN13(10mil,13bytes)	250mm	15mm	code39(10mil,6bytes)	260mm	40mm	code39(15.6mil,6bytes)	350mm	15mm	code128(10mil,6bytes)	270mm	20mm	code128(15.6mil,6bytes)	330mm	30mm	EAN13(15.6mil,13bytes)	360mm
20mm	EAN13(10mil,13bytes)	250mm																		
15mm	code39(10mil,6bytes)	260mm																		
40mm	code39(15.6mil,6bytes)	350mm																		
15mm	code128(10mil,6bytes)	270mm																		
20mm	code128(15.6mil,6bytes)	330mm																		
30mm	EAN13(15.6mil,13bytes)	360mm																		
Wireless Transmitting Distance (Without barrier)	15 - 20M																			
Infrared induction disrance	—																			
Optical Source	650nm Visible red light diode																			
Reading Precision	≥ 4mil																			
Minimum Contrast	≥ 30%																			
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.																			
Decoding Speed	100time/second																			
Barcode Sensitivity	Tilt	±65°																		
	Totate	±42°																		
	Deflection	±60°																		
Data interface	RJ-45																			
<b>Mechanical and Electric Performance</b>																				
Size(Length x Width x Height)	92.5×70×154.6 mm																			
Weight	168g																			
Indicator	Siren and LED light																			
Battery Capacity	600mah																			
Max. Power	350mw																			
Working Voltage	DC5V																			
Current	Max.Current	70ma																		
	Working Current	66ma																		
	Standby Current	45ma																		
	Sleeping Current	≤ 2ua																		
Charging Current	450ma																			
<b>Accessory List</b>																				
Data Cable	Micro USB																			
Wireless Receiver	—																			
CD	1																			
Operation Manual	1																			
Charge station	—																			
<b>Environmental Parameter</b>																				
Storage Temperature	-40°C ~ 60°C																			
Working Temperature	0°C ~ 50°C																			
Relative Humidity	0 ~ 95%																			
Height Range	1.5M																			
IP Rating	IP52																			
<b>Certification</b>																				
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004																				

