

# Rugged Bluetooth Handy-Barcode-Scanner für Android.Windows Mobil.IOSYT-890

# Yumite



## Description

Yumite

Dies ist Echtzeit-Datenübertragung Bluetooth-Technologie und einer der heißesten drahtlosen Laser-Barcode

Scanner [www.china-barcode-scanner.com](http://www.china-barcode-scanner.com) einfach für Android / Windows Mobile / ios integriert

für den direkten Einsatz ohne Treiberinstallation.

## Feature

Yumite

1. Bluetooth Barcode Scanner
2. for Android / iPhone Handy / Tablet PC-Nutzung
3. Rugged Casting
4. Bluetooth mobilen Barcode Scanner
5. Fahrer 5.No
6. PC direkten Einsatz



Para	Model	YT-890
<b>Image</b>		
Image		
<b>Performance Parameter</b>		
Depth Filed		
Wireless Transmitting Distance (Without barrier)	15 - 20M	
Infrared induction distance	—	
Optical Source	650nm Visible red light diode	
Reading Precision	≥ 4mil	
Minimum Contrast	≥ 30%	
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.	
Decoding Speed	100time/second	
Barcode Sensitivity	Tilt	±65°
	Totate	±42°
	Deflection	±60°
Data interface	RJ-45	
<b>Mechanical and Electric Performance</b>		
Size(Length x Width x Height)	92.5×70×154.6 mm	
Weight	168g	
Indicator	Siren and LED light	
Battery Capacity	600mah	
Max. Power	350mw	
Working Voltage	DC5V	
Current	Max.Current	70ma
	Working Current	66ma
	Standby Current	45ma
	Sleeping Current	≤ 2ua
Charging Current	450ma	
<b>Accessory List</b>		
Data Cable	Micro USB	
Wireless Receiver	—	
CD	1	
Operation Manual	1	
Charge station	—	
<b>Environmental Parameter</b>		
Storage Temperature	-40°C ~ 60°C	
Working Temperature	0°C ~ 50°C	
Relative Humidity	0 ~ 95%	
Height Range	1.5M	
IP Rating	IP52	
<b>Certification</b>		
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004		

Our factory

**Yumite**



Application

**Yumite**

