Description

2D módulo de escáner de código de barras YT-M401 es para el autoservicio uso de terminales y cinco personalización de la interfaz.

Shenzhen World Reputation Electronics Technology Co.,Ltd

Model	YT-M401-A	YT-M401-B	YT-M401-C	YT-M401-D
Picture				
IO Trigger	NO	NO	YES	YES
RS232 Trigger	YES	NO	YES	NO
Auto Trigger	YES	YES	NO	NO
Data line	RS232	2.54mm flex cable	RS232& IO control cable	2.54mm flex cable & IO control cable

características

1. Puede leer códigos de barras 1D y 2D
2. Tamaño pequeño puede estructuró en diferentes dispositivos
3. Interfaz de interfaz diferente chooseable: USB, RS232, IO, etc.
4. Alta velocidad: 280 veces / s
5. Apoyo a la personalización
6. La función de detección automática

aplicaciones

Punto de venta, logística, gestión de almacenes, managemnent datos, kiosco, equipo de automatización

Specification

Infrared induction distance		150 - 200mm
Optical Source		620nm Visible red light diode
Imaging Sensor		CMOS(Image)
Resolution Ratio		752×480
Image Resolution		≥ 5mil
Reading Depth	Code 39	40mm -280mm(10mil); 85mm~325mm(15mil)
	PDF417	60mm -225mm(10mil); 60mm~340mm(15mil)
	Data Matrix	20mm -155mm(10mil); 35mm~235mm(15mil)
	QR Code	35mm -150mm(10mil); 20mm~230mm(15mil)
Minimum Contrast		≥ 30%
Barcode Types	2D	PDF417, QR Code(Model 1/2),micro QR， Data Matrix(ECC200, ECC000,050, 080, 100,140).
	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey etc.
Decoding Speed		300times/s
Barcode Sensitivity	Tilt	±55°
	Rotate	±360°
	Deflection	±55°
Data Interface Port		TTL or RS232
three trigger mode		1.Auto-trigger 2.RS232 trigger 3. IO signal trigger
Mechanical and Electric Performance		
Size(Length x Width x Height)		70.3×50×22.4 mm
Weight		47g
Indicator		Siren and LED light
Max.Power		1150mw
Working Voltage		DC5V

Current	Max.Curren	230ma
	Working Current	100ma
	Stand-by Current	50ma
Accessory List		
Data line		RS232(1.8M)
		2.54mm flex cable（1.2m）
		IO control cable
Operation Manual		one
Environmental Parameter		
Storage Temperature		-40°C ~ 60°C
Working Temperature		-25°C ~ 60°C
Relative Humidity		0 ~ 95%
Height Range		2m
IP Rating		IP52
Certificates		
CE,RoHS,EMC,LVD，ISO9001:2008，ISO14001:2004		

Multi-angle

CERTIFICATES

Factory

CUSTOMER

Customer visit

Our customers came to Yumite company to visit and field trips, they are satisfied with our quality and service.

OUR SERVICE

SERVICE

Professional and patient pre-sale and after-sale service on our products;

COOPERATION

Stable quality and reasonable price for you to gain long term cooperation;

OEM&ODM

OEM & ODM service for quantity orders;

QUALITY

Sample orders welcomed for quality test;

WARRANTY

Minimum warranty of one year for free.

How about the quality of the products?

There are CE/ROHS/FCC/IEC/IP52/MSDS/UN38.2/LVD/ISO9001/ISO14001 certifications and reports.

What's the payment way?

We accept Paypal, T/T, L/C, Western Union, MoneyGram.

What's the shipping way?

There are DHL, Fedex, TNT, UPS.(We also can ship the goods by your shipping account or other express agent you provided).

How long can I get the products?

Within seven working days.

How about the after-sales service?

Our product are warranted against manufacturing defects in materials for a period of one year and workmanship for a period two years from date of Manufacture uder normal use. Lifetime maintenance for setting use.