China, láser de código de barras bluetooth portátil escáner de código de barras con la memoria YT-890



Description



Yumite bescáner ARCODE

a.Exquisite y hermoso diseño, externo protegido por goma blanda e interna científica estructura de solidificación, por lo que su resistencia a la caída mejor que escáner ordinario. b.El última realización técnica se aplica a la función de motor y de decodificación, la lectura códigos mejor y más rápido que el tipo similar en el mercado.

c.Easy usando, ajuste fácil.

capacidad d.Large, 1,5 veces mayor que el escáner ordinario, que garantiza el uso de tiempo más largo después de completamente cargado.

Feature



- Soporta estándar de protocolos Bluetooth; No hay conversiones o adaptadores necesarios;
- Código de Barras Digitalización con conexión USB 2.0 Cable y conexión inalámbrica Bluetooth Posible
- La unidad está equipada con las tabletas, dispositivos móviles y ordenadores portátiles;
- Apoyo a Microsoft Windows XP / 7/8, ios de apoyo, Mac, Android, teléfonos inteligentes,

PDA y así sucesivamente.

- "Modo Check" es simple y se puede utilizar con facilidad, y puede storage500-10000 código de barras
- \bullet En la distancia "Normal Mode" de transmisión es 20 \sim 50 M (Dependiendo del entorno de trabajo).

Specification



Performance Parameter Performance Parameter	Para Model	YT-890	
Performance Parameter Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed De		Image	
Depth Filed Some EANI30 Interview EANI30 EANi3	lmage	Yundo Modern Poor Manage	
Mithout barrier	Depth Filed	20mm EANI3(10mil,13bytes)250mm 15mm	
Without barrier	Wireless Transmitting Distance	15 - 20M	
Detail Source Seading Precision ≥ 4mil	(Without barrier)	1.00.2511	
Decoding Precision 2 4mil 2 30%		650pm Visible red light diede	
Second content	~ '		
UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39, MSI, Code11,Code39 Full ASCII, Code39 Troptic, Code128, Code128 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code128, Code128, Code128, Code128, Full ASCII, Code39, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.			
Tilt	Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal	
Totate	Decoding Speed	100time/second	
Content			
Data interface	Sonethythy		
Mechanical and Electric Performance	Data interface	1,000,000	
Veight 168g		Mechanical and Electric Performance	
### Size and LED light ### S	Size(Length x Width x Height)	92.5×70×154.6 mm	
Stattery Capacity Gomah Max. Power 350mw Working Voltage DC5V Current Working Current 45ma Standby Current 450ma Standby Current 450ma Charging Current 100ma Charges Receiver 1 Charges Receiver 1 Charge station 1 Charge station 1 Charge station 1 Charge Temperature 40°C ~ 60°C Working Temperature 0°C ~ 50°C Celative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification 100ma Certification IP52 Certification 100ma Construction 100ma Const	Weight	168g	
Max. Power 350mw	Indicator	Siren and LED light	
Max. Current Max. Current Toma Working Current Standby Current 45ma	Battery Capacity	600mah	
Current 70ma Working Current 66ma Standby Current 45ma Sleeping Current 450ma Charging Current Accessory List Micro USB — Vireless Receiver 1 CD 1 Operation Manual 1 Charge station — Environmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52	Max. Power		
Working Current Standby Current Standby Current Steeping Curr			
Standby Current 45ma Sleeping Current ≤ 2ua Accessory List Data Cable Micro USB Wireless Receiver 1 CD 1 Operation Manual 1 Charge station Environmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52	Working Current		
Accessory List	Standby Current	45ma	
Accessory List Micro USB			
Micro USB	onarging Current		
Vireless Receiver	D-4- C-11-		
CD		Y	
Departion Manual	Wireless Receiver		
Charge station — Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Operation Manual		
Environmental Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Charge station		
Storage Temperature -40 °C ~ 60 °C Working Temperature 0 °C ~ 50 °C Relative Humidity 0 ~ 95 % Height Range 1.5 M P Rating IP52 Certification			
Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Storage Temperature	-40°C ~ 60°C	
Height Range 1.5M P Rating IP52 Certification			
P Rating IP52 Certification			
Certification		1 4 5 5	
	IP Rating		
OL,13010,LVD, 1003001.2000,100 14001.2004	IP Rating	IP52	



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6£ Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:







Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsieng Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bear an District, Sherathen Sherathen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingsiang Business Building, No.1, Dezheng Road, Shilong Community, Shiyan, Bac'an District, Sherathen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-41200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.





Sherzhen United Testing Technology Co., Ltd. Room 177-319, Block 1, University Tree Technology Park. 57-20m. South Rection, Fronty Tree Technology Park. Namelson Destrict. Breaches. PRC 315095 164-40-753-86 https://doi.org/10.1516/10.1516/ 164-40-753-86 https://doi.org/10.1516/









EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Y1-1300, YT-850, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art 3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
Att.3.2	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

with the council #ATTE directive 90/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

Date of issue



Shenzhen United Testing Technology Co., Ltd.
Roses 317-319. Block 1. University Toes Technology Park.
97-20ne, Social Section, Hongranising Industrial Park.
Nasionan Darest Shenzhen, PRC 518091
106 - 987-556-660000 Fax-6156-66160118
106 University Section Section Section Section Sec





Our factory



