

Nuevo y de alta calidad.

Múltiples interfaces para mayor compatibilidad.

Equipado con opcionales agradable beeper confirmar lee éxito.

Excelente fiabilidad campo, incluso en un ambiente al aire libre terrible.

El más rentable y fácil de instalar dispositivos en el mercado.

Plug and play, no hay controladores o software especial necesarios.



	Model	YT-760A			
		Image			
lmage					
		Performance Parameter			
Depth Filed		20mm			
Wireless Trans (without barrie	smitting Distance	_			
Infrared induction Distance		150 - 200mm			
Optical Source		650nm Visible red light diode			
Reading Percision		≥4mil			
Minimum Contrast  Decoding Capacity		≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code .ect.			
Decoding Cap	acity	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal			
8 <b>2</b> 56 133	,,,	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal			
Decoding Spee	ed  Tilt	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65°			
Decoding Spec	ed	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second			
Decoding Capa Decoding Specifications Barcode Sensitivity Data Interface	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code,ect.  100times/second ±65° ±42° ±60° RJ-45			
Decoding Specifications Specification Specif	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter			
Decoding Special Barcode Sensitivity Data Interface Size(Length x	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm			
Decoding Special Barcode Sensitivity Data Interface Size(Length x '	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g			
Decoding Specifications Specification Specif	ed Tilt Rotate Deflection  Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm			
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm 148g Siren and LED light —— 500mw			
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second  ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g  Siren and LED light  —— 500mw DC5V			
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm 148g Siren and LED light —— 500mw			
Decoding Special Barcode Sensitivity Data Interface Size(Length x length to	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma			
Decoding Special Barcode Sensitivity Data Interface Size(Length x   Weight Indicator Battery Capaci Max.Power Working Voltage	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second  ±65°  ±42°  ±60°  RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g  Siren and LED light  ——  500mw DC5V 100ma 97ma 77ma ——			
Decoding Special Barcode Sensitivity Data Interface Size(Length x   Weight Indicator Battery Capaci Max.Power Working Voltage	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light ———— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List			
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second  ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g  Siren and LED light  ——  500mw DC5V 100ma 97ma 77ma —— 450ma			
Decoding Special Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light ———— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List			
Decoding Spece Barcode Sensitivity Data Interface Size(Length x ') Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second  ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light  —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB —— —— ——			
Decoding Specific Spe	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light ———— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List			
Decoding Specific Spe	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second			
Decoding Special Speci	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second  ±65°  ±42°  ±60°  RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g  Siren and LED light  ——  500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB —— ——  1 Set Environmental Parameter			
Decoding Spece Barcode Sensitivity Data Interface Size(Length x ' Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Statior Holder Storage Tempore	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second  ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light  —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB —— 15et Environmental Parameter  -40°C ~ 60°C			
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnirans,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second			
Decoding Special Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempo Working Temp Relative Humic Heigth Range	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma  Accessory List  Mirco USB ————————————————————————————————————			
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second			



## **Application**

