USB Bluetooth inalámbrico escáner de código de barras láser



El escáner de código de barras láser bluetooth es fácil de utilizar. Puede ser emparejado con el dispositivo, que es con el bluetooth, no más software.YT-890 ios de apoyo, Mac, Android, teléfonos inteligentes, terminal de la posición y así sucesivamente.

Performance Parameter Performance Parameter	Para Model	YT-890		
Performance Parameter Performance Parameter		Image		
Pepth Filed September Pepth Pep	lmage	Names Carle Comments Account to the Comments		
Without barrier 15 - 20M	Depth Filed	20mm EAN13(10mil,13bytes)250mm Coole39(10mil,6bytes) 260mm Coole39(15.6mil,6bytes) 350mm Coole128(10mil,6bytes) 270mm Coole128(15.6mil,6bytes) 330mm EAN13(15.6mil,13bytes) 360mm EAN13(15.6mil,13bytes) 360mm Coole128(15.6mil,13bytes) Coo		
Infrared induction disrance Optical Source (acting Precision Decoding Precision Decoding Capacity Decoding Capacity Decoding Speed Decoding Speed Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. Defice Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, e.d. 100time/second 100time/	Wireless Transmitting Distance	15 - 20M		
Decidical Source Seafung Precision ≥ 4mil 2 mil 2 m	· · · · · · · · · · · · · · · · · · ·			
Seading Precision 2 4mil 3 30%	Optical Source	650nm Visible red light diode		
Contract	Reading Precision			
Secoding Speed 100time/second 10time/second 10time/sec	Minimum Contrast Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal		
Tit	Decoding Speed			
Interest	Barcado Tilt	±65°		
Defection Section Se	Sonsitivity			
Mechanical and Electric Performance	Deflection	1000000000		
Size Length x Width x Height 92.5×70×154.6 mm Veight	vata interiace			
Veight 168g	Size/Langth v M/:dth v Ll=:=L4			
Siren and LED light				
Statery Capacity G00mah				
Max. Power 350mw Vorking Voltage DC5V Vorking Voltage T0ma Working Current 45ma Standby Current 45ma Steeping Current 450ma Charging Current 1 Charge Seceiver 1 Charge Seceiver 1 Charge Station 1 Charge station 1 Charge Station 1 Charge Temperature -40°C ~ 60°C Correct Storage Temperature 0°C ~ 50°C Celetative Humidity 0 ~ 95% Leight Range 1.5M PRating IP52 PR				
Vorking Voltage		Contract Con		
Max.Current 70ma Working Current 66ma Standby Current 45ma Sleeping Current ≤ 2ua Accessory List Micro USB Joata Cable — Vireless Receiver 1 5D 1 Operation Manual 1 Charge station — Environmental Parameter Vorking Temperature -0°C ~ 50°C telative Humidity 0 ~ 95% leight Range 1.5M P Rating IP52				
Working Current Standby C				
Standby Current Sleeping Cu	Current Working Current	66ma		
Accessory List	Standby Current			
Accessory List Micro USB				
Micro USB	onarging Current			
Vireless Receiver	2.4.0.11			
CD	Data Cable			
Department 1	Wireless Receiver			
Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C telative Humidity 0 ~ 95% leight Range 1.5M P Rating IP52	CD			
Environmental Parameter Storage Temperature -40°C ~ 60°C Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Releight Range 1.5M P Rating IP52	Operation Manual	1		
Contrage Temperature	Charge station	Facility and Day 1		
Vorking Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% Relative Range 1.5M ☐ Rating IP52	Storago Tomporatura			
Relative Humidity 0 ~ 95% Relative Humidity 1.5M P Rating IP52				
leight Range 1.5M P Rating IP52				
P Rating IP52				
to the second se				
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004	CE			