## Bluetooth transmission barcode scanner





The bluetooth laser barcode scanner is easy for using. It can be paired with your device whi ch is with bluetooth, no more software.YT-890 support ios, Mac, Android, smart phone,PDA and so on.



Performance Parameter    Performance Parameter	Para Model	YT-890		
Performance Parameter  Depth Filed  Depth Filed Depth Filed  Depth Filed  Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed De		Image		
Depth Filed    Some   EANI30   Interview   EANI30   EANi3	lmage	Yanab Makan Pool Headan		
Mithout barrier	Depth Filed	20mm EANI3(10mil,13bytes)250mm  15mm		
Without barrier	Wireless Transmitting Distance	15 - 20M		
Detail Source   Seading Precision   ≥ 4mil	(Without barrier)	1.00.2511		
Decoding Precision   2 4mil   2 30%		650pm Visible red light diede		
Second content	~ <del>'</del>			
UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39, MSI, Code11,Code39 Full ASCII, Code39 Troptic, Code128, Code128 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code128, Code128, Code128, Code128, Full ASCII, Code39, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.				
Tilt	Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal		
Totate	Decoding Speed	100time/second		
Content				
Data interface	Sonethythy			
Mechanical and Electric Performance	Data interface	1,000,000		
Veight   168g		Mechanical and Electric Performance		
### Size and LED light  ### S	Size(Length x Width x Height)	92.5×70×154.6 mm		
Stattery Capacity   Gomah     Max. Power   350mw     Working Voltage   DC5V     Current   Working Current   45ma     Standby Current   450ma     Standby Current   450ma     Charging Current   100ma     Charges Receiver   1     Charges Receiver   1     Charge station   1     Charge station   1     Charge station   1     Charge Temperature   40°C ~ 60°C     Working Temperature   0°C ~ 50°C     Celative Humidity   0 ~ 95%     Height Range   1.5M     P Rating   IP52     Certification   100ma     Certification   IP52     Certification   100ma     Construction   100ma     Const	Weight	168g		
Max. Power   350mw	Indicator	Siren and LED light		
Max. Current   Max. Current   Toma   Working Current   Standby Current   45ma	Battery Capacity	600mah		
Current         70ma           Working Current         66ma           Standby Current         45ma           Sleeping Current         450ma           Charging Current           Accessory List           Micro USB           —           Vireless Receiver         1           CD         1           Operation Manual         1           Charge station         —           Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52	Max. Power			
Working Current   Standby Current   Standby Current   Steeping Curr				
Standby Current         45ma           Sleeping Current         ≤ 2ua           Accessory List           Data Cable         Micro USB           Wireless Receiver         1           CD         1           Operation Manual         1           Charge station         Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52	Working Current			
Accessory List	Standby Current	45ma		
Accessory List   Micro USB				
Micro USB	onarging Current			
Vireless Receiver	D-4- C-11-			
CD		Y		
Departion Manual	Wireless Receiver			
Charge station         —           Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Vorking Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52           Certification	Operation Manual			
Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52           Certification	Charge station			
Storage Temperature         -40 °C ~ 60 °C           Working Temperature         0 °C ~ 50 °C           Relative Humidity         0 ~ 95 %           Height Range         1.5 M           P Rating         IP52           Certification				
Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Storage Temperature	-40°C ~ 60°C		
Height Range 1.5M P Rating IP52 Certification	Working Temperature			
P Rating IP52  Certification				
Certification		1 4 5 5		
	IP Rating			
OL,13010,LVD, 1003001.2000,100 14001.2004	IP Rating	IP52		



# Certification



### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05

This is to certify the quality management systems of

### Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:









### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 €1 0796 805 This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Bechnology Co., LTD Located in 6f. Xingqiang Commercial Manison, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:





## Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Raputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shiong Community, Shyan, Savan District, Shenzhen Shenzhen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shiong Community, Shiyan, Bao'an District, Shenzhen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-41200, YT-1100A, YT-1100B, YT-M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.



**RoHS** 

Date of saue





### **EC-R&TTE** Certificate

Certificate Number: UNIZEL4122403EC-1

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputations Electronical Technology Co., Ltd.
6F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Bar-code Scanner
Vivorite

Yumits YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential re-	quirement	Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 480-1/-3	UNI2014122403ER-1	Pass
At132	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in complice with the council RATTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

Date of issue









welcome to contact with us!