

Features

Bluetooth wireless technology and unique bluetooth solution
Easy match code
Better drop-resistance
Used for PC,mobile phone,tablet
Fast speed 100times/second
One to One pairing, easy setting
Flicking Scanning and Auto Scanning and Continuous Scanning
Large capacity 8MB, equal to save more than 300000 bar codes
Longer transmitting distance 20M
Supporting customization
Fully plug&play compliant

Applications

Supermarket, Retail, Healthcare, Logistics, Postal Communication, Government, Clothing industry, Power Industry, Hospital, Bookstore, School



| | |
|---|---|
| Wireless Transmitting Distanc (without barrier) | 15 - 20m |
| Infrared induction distance | -- |
| Optical Source | 650nm Visible red light diode |
| Image Resolution | ≥4mil |
| Minimum Contrast | ≥ 30% |
| Barcode Types | UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes. |
| Decoding Speed | 100times/s |

| | | |
|---------------------|------------|-------|
| | Tilt | ±65° |
| Barcode Sensitivity | Rotate | ±42° |
| | Deflection | ±60° |
| Data Interface Port | | RJ-45 |

Mechanical and Electric Performance

| | | |
|-------------------------------|------------------|---------------------|
| Size(Length x Width x Height) | | 92.5×70×154.6 mm |
| Weight (except cable) | | 168g |
| Indicator | | Siren and LED light |
| Battery Capacity | | 600mah |
| Max.Power | | 350mw |
| Working Voltage | | DC5V |
| | Max.Curren | 70ma |
| Current | Working Current | 66ma |
| | Stand-by Current | 45ma |
| | Sleeping Current | ≤ 2ua |
| Charging Current | | 450ma |

Accessory List

| | | |
|------------------|--|-------------------|
| Data line | | USB data line(1m) |
| | | -- |
| Receiver | | 1Piece |
| Drive CD | | 1Piece |
| Operation Manual | | 1Piece |
| Charging Cradle | | -- |

Environmental Parameter

| | | |
|---------------------|--|--------------|
| Storage Temperature | | -40°C ~ 60°C |
| Working Temperature | | 0°C ~ 50°C |
| Relative Humidity | | 0 ~ 95% |
| Height Range | | 1.5m |
| IP Rating | | IP52 |



1

Super decoding
function

2

High-end
craft tips



3

High elastic
button



4

Buzzer
prompt

