

YT-2200

2D IMAGE DESKTOP

专业物联网设备制造商
The Professional IoT Equipment Manufacturer



PERFORMANCE		
IMAGE SENSOR	640 * 480 CMOS	
LIGHT SOURCE	4PCS WHITE LED	
SYMBOLS	2D	PDF417, Data Matrix, QRCode, Micro QR
	1D	Code 128, UCC/EAN-128, AIM 128, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-14, Matrix 2 of 5 (European Matrix 2 of 5), Industrial 2 of 5, Standard 2 of 5, Code 39, Codabar, Code 93, Code 11, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand etc.
RESOLUTION	1D ≥ 5mil 2D ≥ 10mil	
DEPTH OF FIELD	EAN13	20mm-200mm (13mil)
	Code 39	10mm-100mm (5mil)
	QR Code	5mm-180mm (15mil)
	PAYMENT CODE (PHOE)	20mm-450mm
PCS	10%	
INTERFACE	USB-HID , USB-VCOM, UART (DUE TO ORDER)	
MECHANICAL / ELECTRICAL		
SIZE	110*150*122(mm)	
WORKING MODE	TRIGGER MODE , AUTO-SENSOR , CONTINUOUS SCAN	
WEIGHT	348g (WITH CABLE)	
INOUT VOLTAGE	5VDC ± 10%	
CURRENT	Operating: 210mA ± 10mA;	
	Standby: 130 ± 5mA;	
ENVIRONMENTAL		
OPERATING TEMPERATURE	0° C to 45° C	
STORAGE TEMPERATURE	-20° C to 60° C	
HUMIDITY	5%~90% (no-condensing)	
SHOCK RESISTANCE	1.0M FREE FALL TEST	
CERTIFICATE		
CERTIFICATE	FCC Part15 Class B, CE EMC Class B	
VERSIONS OF SPECIFICATION		
VERSIONS	V1.1	

NOTICE:

Please make sure that the voltage meets the technical requirements when using the