

# Description

competitive price wired laser barcode scanner is a wired laser barcode scanner can be used in supermarket, logistic , bookstore,hospital etc, in a word where there is a barcode there is a Wired laser barcode scanner with USB cable scanner can be used.

## Function

The performance of competitive price wired laser barcode scanner is very high, not only with faster scanning speed but also have low price cost . the scanner is rubberized with solid shell which can be dropped from 2m high place. and it can read UPC/EAN/JAN,UPC/EAN with supplementals, Discrete 2 of 5 IATA,RSSvariants,Codabar,chinese 2 of 5,Interleaved 2/5 etc.

## Specification

|                          |   |                             |
|--------------------------|---|-----------------------------|
| ould Number              | YT760   | Wired laser barcode scanner |
| Technical parameter      |   |                             |
| Light Source Type        | Visual lasing diode;the wave length is 650mm.   |                             |
| Trigger Mode             | Manul   |                             |
| Scanning Mode            | Single-line scanning  |                             |
| Scanning Speed           | 100±2 times/s   |                             |
| Scan Precision           | ≥4mil   |                             |
| Printing Contrast Ratio  | The lowest reflectivity differece is 30%.   |                             |
| Bit Error Rate           | 1/50 million  |                             |
| Environment Luminance    | 3000-12000 Lux  |                             |
| Depth of field           | 5mm-630mm   |                             |
| Scanning Angle           | ±60°±65°±42° (Left and right, front and back, rotation)   |                             |
| Decoding capacity        | UPC/EAN/JAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, MSI, Code11, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128Full ASCII, Codabar, Code93, Discrete2of5, IATA, RSSvariants, Codabar, Chinese2of5, International general dimensional barcodes, e.g. Inteleaved2/5, Interleaved2of5 and China postal sevice code |                             |
|                          |   |                             |
| Electical parameter      |   |                             |
| Input voltage            | 5VDC±0.25V  |                             |
| Power                    | 250mW(work): 325mW(momentary maximum)   |                             |
| Current                  | 50mA(work): 65mA(momentary maximum)   |                             |
| Standby Current          | <20mA   |                             |
| Prompt Mode              | Buzzer and LED indicator  |                             |
| Physical parameter       |   |                             |
| Transfer cable interface | USB   |                             |
| Dimension                | L*W*H: 158mm*68mm*96mm  |                             |
| Weight                   | 170g(excluding cables)  |                             |
| Cable standard           | Straight line,1m  |                             |
| Interface type           | RJ-45 crystal head  |                             |
| Outside material         | ABS+PC  |                             |
| Environment parameter    |   |                             |
| Temperature              | 0°C to 50°C(work):-40°C to 60°C(storage)  |                             |
| Anti-knock capacity      | This product can still work properly after falling from the height of 2m  |                             |

## Certification:

