competitive price wired usb cable CCD Barcode Scanner manufacturer china



Description



Wired CCD barcode scanner, barcode

reader YT-1001 is able to improve speed, accuracy and productivity.

The scan engine features no moving parts for years of reliable service reading popular 1D barcodes including UPC, EAN, ASCII, MSI/PLESSEY, GS1 DataBar and more.

Easy to implement and simple to use, a built-

in keyboard wedge decoder sends scanned data to an active application where it appears as if it were manually typed or directly keyed into the computer.

Its versatile switchable USB or RS232 cable interface integrates with most PCs without an ext ernal power supply. With a scan rate of 280 times per second and an accurate read range of up to 50 cm (20 in.), this model offers an effective and efficient, all-

purpose daily scanning solution for less demanding point-of-

sale, office and other low ambient light applications to minimize manual data entry, speed transactions and reduce errors.

Feature



The features and lower cost make this wired CCD Barcode Scanner the best solution for retail, medical and light industrial applications. Pic k up one today!

The Yumite wired CCD barcode scanner, barcode reader delivers basic, highquality scanning for a wide range of data collection functions to help improve routine transact ions, automate paper-based processes and increase productivity.

Get superior optical performance with a minimum resolution and a maximum reading distanc e with this contact CCD barcode scanner. It features a rugged and reliable design and a plug and play USB interface. It's easy to setup and use.

Specification



		The control of the co	
Image Depth Filed		Performance Parameter Code 39(10 nil,6by tes) 310 nin	
Infrared induction distance		——————————————————————————————————————	
Optical Source		620nm Visible red light diode	
Imaging Senso	or	CCD	
Image Resolut		2500Pixel	
Reading Preci		≥ 5mil	
Minimum Conf	ırası	≥ 30%	
	acity	Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect.	
Decoding Cap			
Decoding Cap		280times/second	
Decoding Spe Barcode	Tilt	±55°	
Decoding Spe			
Decoding Spe Barcode	Tilt Rotate Deflection	±55° ±25°	
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75°	
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75° RJ-45	
Decoding Spe Barcode Sensitivity Data Interface	Tilt Rotate Deflection	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator	Tilt Rotate Deflection Width x Height)	±55° ±25° ±75° 175° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height)	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height)	±55° ±25° ±75° RJ-45 RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height)	±55° ±25° ±775° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw DC5V	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	Tilt Rotate Deflection Width x Height)	±55° ±25° ±75° RJ-45 RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ——— 650mw	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma ————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current	±55° ±25° ±75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Steeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent eiver	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light —— 650mw DC5V 130ma 86ma 42ma —— Accessory List Micro USB RS232 Cable —— 1 —— Environment Parameter -40°C ~ 60°C	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp	Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Current Sleeping current ent eiver mual n erature perature	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi	Tilt Rotate Deflection Width x Height) wity ge Max.Current Working Current Standby Current Steeping current ent erature erature dity	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Current Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi Height Range	Tilt Rotate Deflection Width x Height) wity ge Max.Current Working Current Standby Current Steeping current ent erature erature dity	#55° #25° #75° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————	
Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Volta Current Charging Curr Data Cable Wireless Rece CD Operation Mar Charge Station Storage Temp Working Temp Relative Humi	Tilt Rotate Deflection Width x Height) wity ge Max.Current Working Current Standby Current Steeping current ent erature erature dity	#55° #25° #75° RJ-45 Mechanical and Electric Performance 92.5×70×154.6 mm 127g Siren and LED light ———————————————————————————————————	



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 €1 0796 ROS This is to certify the environmental management systems of

Shenzhen World Reputation Electronics

Technology Co., LTD Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenshen World Reputation Electronics Technology Co., UTO Located in 6E, Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Boosen District, Shenzhen







EC-R&TTE Certificate

Sherushen World Reputation Electronics Technology Co., Ltd.
6F. 8 Building, 8 Area, Xingqiang Business Building, No. 1, Desheng Road,
Shlong Community, Shiyan, Bao an District, Sherushen
Shenzhen World Regutation Electronicids Technology Co., Ltd.
6F. 8 Building, 8 Area, Xingqiang Business Building, No. 1, Dezheng Road,
Shlong Community, Shiyan, Bao an District, Sherushen
Bar-code Scanner
Vereits

Yumits YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art 3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
At.3.2	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in complice with the council RATTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.





welcome to contact us!