1D Mini Laser Barcode Scanning Engine YT-M200



Description



Yumite 1D Mini Laser Barcode Scanning Engine/ Laser Scan Engine/ Barcode Scanner Module is one of typical

China barcode scanner. Easily integrated in Supermarket, retail/chain shops/KIOS system with a competitive price.

Feature



Laser image sensor and various inetrface connection supported RJ45 and USB. With 100times/second decoding speed, an ideal chloice for applications.

Two cables USB-USB and USB-

OTG to use with Android/Iphone/Tablet PC or computer without diver for a direct use.

Plug and play and ease of use for average use.

Specification



	Model	YT-M200	
		Image	
lmage			
Depth Filed		### Performance Parameter #### EAN13(10mil,13loytes)250mm ##################################	
Wireless Transmitting Distance (without barrier)		12	
nfrared induct	tion Distance	150 - 200mm	
	e	aboid tribil del eldisiv mruco	
Optical Source		650nm Visible red light diode ≥4mil	
Optical Source Reading Perci Minimum Conf	ision		
ptical Source leading Perci linimum Conf lecoding	ision trast	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal	
ptical Source eading Perci linimum Conf ecoding	ision trast eed Tilt	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65°	
ptical Source leading Perci linimum Conf lecoding lecoding Spe arcode	ision trast eed Tilt Rotate	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42°	
Optical Source Reading Perci Inimum Conf Decoding Decoding Speciarcode Rensitivity	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60°	
Optical Source Reading Perci Inimum Conf Decoding Decoding Speciarcode Rensitivity	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42°	
ptical Source leading Perci linimum Conf lecoding lecoding Spe lecode lensitivity	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Bensitivity Data Interface	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Bensitivity Oata Interface Size(Length x Veight	eed Tilt Rotate Deflection	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Bensitivity Oata Interface Size(Length x Veight Indicator	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Weight Indicator Battery Capac Max.Power	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Weight Indicator Battery Capac Max.Power	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Bensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power	eed Tilt Rotate Deflection Width x Height)	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code31,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma	
Detical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power	eed Trilt Rotate Deflection Width x Height) city ent Max.Current Working Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Barcode Bensitivity Oata Interface Size(Length x Veight Indicator Battery Capac Max.Power Vorking Current	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma ——	
ptical Source leading Perci linimum Conf lecoding lecoding Speciarcode lensitivity lata Interface lize(Length x leight lidicator lattery Capace lax.Power lovering Current	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma	
Detical Source Reading Perci Reading Perci Reading Special Source Recoding Special Recode Recoding Spe	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— —— —— —— ——— ————————————————————	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Data Cable	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current rent	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Currer Current Charging Curre Data Cable Wireless Rece CD	eed Tilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Sleeping Current rent	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List USB—OTG Micro USB —— —— —— —— —— —— —— —— ——— —————————	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curre Data Cable Wireless Reco CD Operation Mai	eed Tritt Rotate Deflection Width x Height) with x Height and the second and th	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— —— —— —— ——— ————————————————————	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curre Data Cable Wireless Reco CD Operation Mai	eed Tritt Rotate Deflection Width x Height) with x Height and the second and th	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——— mw DC5V 95ma 93ma 47ma ——— 450ma Accessory List USB—OTG Micro USB ——— 1 ——— 1	
Optical Source Reading Perci Minimum Conf Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Current Data Cable Wireless Rece CD Operation Mai Charge Station	eed Trilt Rotate Deflection Width x Height) Eity Ent Max.Current Working Current Standby Current Standby Current Steeping Current rent Eiver	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——— ————————————————————————————————	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Current Charging Curre Operation Mai Charge Station Storage Temp	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Standby Current rent eiver	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codebar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List USB-OTG Micro USB —— —— Environmental Parameter -40°C ~ 60°C	
Optical Source Reading Perci Minimum Cont Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre	eed Trilt Rotate Deflection Width x Height) ent Max.Current Working Current Standby Current Standby Current rent eiver nual n perature perature	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code 128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light ——— ————————————————————————————————	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Curre Current Charging Curre C	eed Trilt Rotate Deflection Width x Height) Eity Ent Max.Current Working Current Standby Current Steeping Current rent Eeiver In a contract of the contra	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° USB Mechanical and Electric Parameter 70.3×50×22.4 mm 51g Siren and LED light —— mw DC5V 95ma 93ma 47ma —— 450ma Accessory List USB—OTG Micro USB —— 1 —— Environmental Parameter 40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5M	
Optical Source Reading Perci Reading Perci Minimum Cont Decoding Decoding Decoding Spe Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capac Max.Power Working Current Charging Curre Current Charging Curre Charging Cu	eed Trilt Rotate Deflection Width x Height) Eity Ent Max.Current Working Current Standby Current Steeping Current rent Eeiver In a contract of the contra	≥4mil ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second	



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of $ISO9001\!:\!2008$

R&D, Production of Barcode Scanning Identification Equipment

Signed by:

Approval Date: 26 Dec. 201-Depicy Date: 25 Dec. 201-

6





The coefficient informations can be declared on the CNA solution (MMMCNC) in CNCC. The solutions of the coefficient can be obtained through twent-knows on the contract of the coefficient in the coefficient of coefficient operators of the coefficient of the coefficient operators operators on the coefficient operators operators operators on the coefficient operators operators operators on the coefficient operators o

CAS

CERTIFICATE OF REGISTRATION

Certificate No. . 117 14 €1 0796 805 This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Ximgqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning identification Equipment for Shenzhen World Reputation Electronics Bechaology Co., UTD Located in 6f. Xingqiang Commercial Manison, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Booan District, Shenzhen

Signed by:

Control of Control of

Mr. M. D. SERVICE Sec. - M. D. M. SERVICE No. - M. D. M. SERVICE No. - M. D. Expley Date: 25 Dec. 20

130w





PTTNCNCALANCE. The subdence of the confidence planters of the confidence planters to the confidence of the confidence planters to the confidence of the conf



Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, Bilbulding, BiArea, Xingqiang Business Building, No.1, Dezheng Road,
Shiting Community, Shiyan, Barain District, Shenzhen
Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, Bibulding, BiArea, Xingqiang Business Building, No.1, Dezheng Road,
Shiting Community, Shiyan, Barian District, Shenzhen
Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.



Date of saue









EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputations Electronics Technology Co., Ltd.
6F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Bar-code Scanner
Vivorite

Yumits YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 480-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in complice with the council RATTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24

Date of issue

americaned United Leading Leaflinghopy of Rober 317-376 Block 1, University Tean Februsiagy 5° Zens, South Section, Honghuaing Industrial Paix, Nanhan Denick, Shenchen, PMC 31809 8 at 98.756-8010090 Fax 198-755-98180138 Total Paine and 360 fax 198-755-98180138 Total Paine and 360 fax





Our factory



