32 Bit Colour Depth and Stock Products Status 2D Barcode module





Description



YT-M401 is a 2D mini wired barcode module which can be applied in devices including: POS, medical devices, kiosks, lottery terminals and access control devices, a stand option can be ordered to facilitate desktop hand-free reading options.

Function



YT-M401 is auto-sense scanner that can read the barcode by itself and the Infrared induction distance 150 - 200mm. even the barcode is on the screen or damaged can also be decoded quickly.

Specification



Para	model	YT-M401 wired 2D scan module barcode reader		
		Picture		
Product Picture				
		Performance Parameter		
Infrared induction	on distance	150 - 200mm		
Optical Source		620nm Visible red light diode		
Imaging Sensor		CMOS(Image)		
Resolution Ratio		752×480		
Image Resolutio	n	≥ 5mil		
	Code 39	40mm -280mm(10mil); 85mm~325mm(15mil)		
Reading Depth	PDF417	60mm -225mm(10mil); 60mm~340mm(15mil)		
	Data Matrix	20mm -155mm(10mil); 35mm~235mm(15mil)		
	QR Code	35mm -150mm(10mil); 20mm~230mm(15mil)		
Minimum Contr	rast	≥ 30%		
		PDF417, QR Code(Model 1/2),micro QR,		
Barcode Types	2D	Data Matrix(ECC200, ECC000,050, 080, 100,140).		
	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey etc.		
Decoding Speed		300times/s		
Decoding speed	Tilt	±55°		
Barcode Sensitivity	Rotate	±360°		
	Deflection	±55°		
Data Interface P		TTL or RS232		
three trigger mode		1.Auto-trigger 2.RS232 trigger 3. IO signal trigger		
		Mechanical and Electric Performance		
Size(Length x Width x Height)		70.3×50×22.4 mm		
, , ,				
Weight		47g		
Indicator		Siren and LED light		
Max.Power		1150mw		
Working Voltage		DC5V		
Current	Max.Curren	230ma 100ma		
	Working Current Stand-by Current	100ma 50ma		
	Stand-by Current	Accessory List		
		RS232(1.8M)		
Data line		2.54mm flex cable (1.2m)		
		IO control cable		
Operation Manu	ıal	one		
		Environmental Parameter		
Storage Temperature		-40°C ~ 60°C		
Working Temperature		-25°C ~ 60°C		
Relative Humidity		0~95%		
•				
Height Range		2m		
IP Rating		IP52		
		Certificates		
	CE,RoHS,	EMC,LVD, ISO9001:2008, ISO14001:2004		

Certification





Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqieng Business Building, No.1, Dezheng Road,
Shlong Community, Shiyan, Bara an District, Shenzhen
Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shlong Community, Shiyan, Baran District, Shenzhen
Bar-code Scanner

YU-1000, YT-760, YT-7608, YT-7608, YT-8200, YT-11008, YT-11008, YT-8300, YT-2000, YT-21008, YT-8400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Directive 2011/65/EU. It is only valid in connection with the test report number. UNI2014122403RR-3.











EC-R&TTE Certificate

Certificate Number: UN32014122403EC-1

Shenzhen World Reputation Electronics Technology Co., Ltd. 65; 8 Building, 8 Area, Xingpiang Business Building, No. 1, Dezheng Road, Shlong Community; Shyan, Bao'an District Shenzhen
 Shenzhen World Reputation Electronics Technology Co., Ltd. 6F; 8 Building, 8 Area, Xingpiang Business Building, No. 1, Dezheng Road, Shlong Community, Shiyan, Seo'an District, Shenzhen
 Bar-code Scanner

Yumite: YT-1300, YT-860, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in complian with the council RATTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.



Our factory





Application



Our goods to all over the world







