# Black USB Automatic Sensing and Scan Wired Handheld Laser Barcode Scanner YT-760A



## Description



Auto-sense wired laser barcode scanner YT-760A can be connected with POS systems and very convenient to use.

#### **Feature**



Auto-sense wired laser barcode scanner YT-760A is very easy to use, only need to put the scanner in the stand and then it read the barcode by itself.

### **Specification**



	Model	YT-760A	
		Image	
lmage			
		Performance Parameter	
Depth Filed		20mm EANI3(10mil,13loytes)250mm   15min   coole39(10mil,6loytes) 260mm   15min   coole39(15.6mil,6bytes) 350mm   coole128(10mil,6loytes) 270mm   20min   20min   EANI3(15.6mil,6loytes) 330mm   EANI3(15.6mil,13loytes) 360mm   0 100 200 300 400	
Wireless Trans (without barrier	smitting Distance		
Infrared induction Distance		150 - 200mm	
Optical Source		650nm Visible red light diode	
Reading Percision		≥4mil	
	root		
Minimum Conti	Webs	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal	
Minimum Conti	acity	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second	
Minimum Control  Decoding Capa  Decoding Spec	acity ed Tilt	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65°	
Minimum Control  Decoding Capa  Decoding Specification	acity ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second	
Minimum Control  Decoding Capa  Decoding Specifications  Barcode  Sensitivity	acity ed Tilt	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45	
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate Deflection	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter	
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm	
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x 1) Weight	acity ed Tilt Rotate Deflection	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second  165° 142° 160° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g	
Decoding Capa  Decoding Specific Specif	ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm	
Decoding Capa  Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity  ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw	
Decoding Capa  Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity  ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V	
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to the second to the	acity  ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw	
Decoding Capa  Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma	
Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second  165° 142° 160° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light  —— 500mw DC5V 100ma 97ma 77ma ——	
Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List	
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to the second	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma	
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current  Charging Current  Data Cable Wireless Rece	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List	
Decoding Capa  Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB —— —— —— ———————————————————————————	
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x to the sensitivity Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———	
Decoding Capa  Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second	
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Current  Data Cable  Wireless Rece CD Operation Man Charge Station Holder	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Steeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second  165° 142° 160° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light  ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma  Accessory List  Mirco USB ————————————————————————————————————	
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x ) Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Curre  Data Cable Wireless Rece CD Operation Man Charge Station	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Standby Curent ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second	
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Curre  Data Cable Wireless Rece CD Operation Man Charge Station Holder  Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%	
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface  Size(Length x Very Weight Indicator Battery Capaci Max.Power Working Voltage Current  Charging Current  Charging Current  Charging Current  Data Cable  Wireless Rece CD Operation Man Charge Station Holder  Storage Temper Relative Humic Heigth Range	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma  Accessory List  Mirco USB ———— 1Set  Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5M	
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Curre  Data Cable Wireless Rece CD Operation Man Charge Station Holder  Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%	



#### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6E

6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:



#### CERTIFICATE OF REGISTRATION

Certificate No. 117 14 €1 0796 ROS This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenshen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Manison, No. 1 Derheng Road, Shilong Community, Shiyan Street, Bacum District, Shenzhen

Signed by:

Approval Date: 2s Dec. 2014 Exploy Date: 25 Dec. 2017





# Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, Bilbulding, BiArea, Xingqiang Business Building, No.1, Dezheng Road,
Shiting Community, Shiyan, Barain District, Shenzhen
Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, Bibulding, BiArea, Xingqiang Business Building, No.1, Dezheng Road,
Shiting Community, Shiyan, Barian District, Shenzhen
Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.

2014-12-24



**RoHS** 

Date of saue





#### **EC-R&TTE** Certificate

Certificate Number: UNIZEL4122403EC-1

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputations Electronics Technology Co., Ltd.
6F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Bar-code Scanner
Vivorite

Yumits YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in complice with the council RATTE directive 99/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24

Date of issue



americaned United Leading Leaflinghopy of Rober 317-376 Block 1, University Tean Februsiagy 5° Zens, South Section, Honghuaing Industrial Paix, Nanhan Denick, Shenchen, PMC 31809 8 at 98.756-8010090 Fax 198-755-98180138 Total Paine and 360 fax 198-755-98180138 Total Paine and 360 fax





**Our factory** 



