# Bluetooth laser barcode scanner supplier Support iOS, Android, Win7, Win8 YT-890



## Description



The bluetooth laser barcode scanner is easy for using. It can be paired with your device which is with bluetooth, no more software.YT-890 support ios, Mac, Android, smart phone,PDA and so on.

## Specification



Performance Parameter    Performance Parameter	Para Model	YT-890
Performance Parameter  Depth Filed  Depth Filed Depth Filed  Depth Filed  Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed Depth Filed De		Image
Depth Filed    Septh Filed   S	lmage	Name of the state
Mithout barrier	Depth Filed	20mm EAN13(10mil,13bytes)250mm  15mm
Without barrier	Wireless Transmitting Distance	15 - 20M
Detail Source   Seading Precision   ≥ 4mil   ≥ 30%	(Without barrier)	15 (2011)
Decoding Precision   2 4mil   2 30%		GEOrges Visible and light dind
Second content	~ <del></del>	
UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39, MSI, Code11,Code39 Full ASCII, Code39 Troptic, Code128, Code128 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code37 Full ASCII, Code39, Troptic, Code128, Code128, Code128, Code128, Code128, Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5, Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.		No. Park Company Compa
Tilt	Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal
Totate	Decoding Speed	
Content		
Deletion   State   S	Soneitivity	
Mechanical and Electric Performance	Deflection	10,400,000
Size (Length x Width x Height)   92.5×70×154.6 mm		
Veight   168g	Size(Length x Width x Height)	
### Size and LED light  ### S		STROMEN.
## Startery Capacity ## G00mah    Max. Power		-
Max. Power   350mw		
Max. Current   Max. Current   Toma   Working Current   Standby Current   45ma	The state of the s	
Current         70ma           Working Current         66ma           Standby Current         45ma           Sleeping Current         450ma           Charging Current           Accessory List           Micro USB           —           Vireless Receiver         1           CD         1           Operation Manual         1           Charge station         —           Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52	Working Voltage	DC5V
Standby Current         45ma           Sleeping Current         ≤ 2ua           Accessory List           Data Cable         Micro USB           Wireless Receiver         1           CD         1           Operation Manual         1           Charge station         Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Vorking Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52	Max.Current	
Standby Current   45ma     Sleeping Current   ≤ 2ua     Charging Current   450ma     Accessory List     Data Cable		
Accessory List	Standby Current	
Accessory List   Micro USB	Charging Current	
Micro USB		Accessory List
Nireless Receiver	Data Cable	Micro USB
CD		
Departion Manual		
Charge station         —           Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Vorking Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52           Certification		
Environmental Parameter           Storage Temperature         -40°C ~ 60°C           Working Temperature         0°C ~ 50°C           Relative Humidity         0 ~ 95%           Height Range         1.5M           P Rating         IP52           Certification	Charge station	
Storage Temperature         -40 °C ~ 60 °C           Working Temperature         0 °C ~ 50 °C           Relative Humidity         0 ~ 95 %           Height Range         1.5 M           P Rating         IP52           Certification		
Relative Humidity 0 ~ 95% Height Range 1.5M P Rating IP52 Certification	Storage Temperature	-40°C ~ 60°C
Height Range 1.5M P Rating IP52 Certification	Working Temperature	
P Rating IP52  Certification		0 ~ 95%
Certification		
		1.5M
OF DOLOTER FACE AND LANCE FOR A STATE OF THE	IP Rating	1.5M IP52



#### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansson, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







### CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6f, Xingqiang Commercial Mansion, No. 1 Dealying Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenshen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Bossen District, Shenzhen

Signed by:











## **Our factory**



Shenzhen World Reputation Electronics Technology Co., Ltd. is a china barcode scanner manufacture. It is bluetooth scanner supplier China.

