

China barcode laser portable bluetooth barcode scanner with memory YT-890

Yumite



Description

Yumite

Yumite barcode scanner

a.Exquisite and beautiful design, external protected by soft rubber and internal scientific solidification structure, so its drop resistance better than ordinary scanner.

b.The latest technical accomplishment is applied to the engine and decoding function, reading

codes better and faster than the similar type in the market.

c.Easy using, easy setting.

d.Large capacity, 1.5 times higher than ordinary scanner, it guarantees use longer time after fully charged.

Feature

Yumite

- Supports Standard Bluetooth Protocols; No Conversions or Adapters Needed;
- Bar Code Scanning Using USB2.0 Cable Connection and Bluetooth Wireless Connection Possible
- The unit is equipped with tablets, mobile devices and mobile computers;
- Support Microsoft Windows XP/7/8, support

ios, Mac,Android,smart phone,PDA and so on.

- “Check Mode”is simple and can be used easily,and can storage500-10000 barcode
- Under the “Normal Mode” transmit distance is 20~50 M(Depending on the working environment).

Specification

Yumite

Para	Model	YT-890																		
Image																				
Image																				
Performance Parameter																				
Depth Filed	<table border="1"> <tr> <td>20mm</td> <td>EAN13(10mil,13bytes)</td> <td>250mm</td> </tr> <tr> <td>15mm</td> <td>code39(10mil,6bytes)</td> <td>260mm</td> </tr> <tr> <td>40mm</td> <td>code39(15.6mil,6bytes)</td> <td>350mm</td> </tr> <tr> <td>15mm</td> <td>code128(10mil,6bytes)</td> <td>270mm</td> </tr> <tr> <td>20mm</td> <td>code128(15.6mil,6bytes)</td> <td>330mm</td> </tr> <tr> <td>30mm</td> <td>EAN13(15.6mil,13bytes)</td> <td>360mm</td> </tr> </table>		20mm	EAN13(10mil,13bytes)	250mm	15mm	code39(10mil,6bytes)	260mm	40mm	code39(15.6mil,6bytes)	350mm	15mm	code128(10mil,6bytes)	270mm	20mm	code128(15.6mil,6bytes)	330mm	30mm	EAN13(15.6mil,13bytes)	360mm
20mm	EAN13(10mil,13bytes)	250mm																		
15mm	code39(10mil,6bytes)	260mm																		
40mm	code39(15.6mil,6bytes)	350mm																		
15mm	code128(10mil,6bytes)	270mm																		
20mm	code128(15.6mil,6bytes)	330mm																		
30mm	EAN13(15.6mil,13bytes)	360mm																		
Wireless Transmitting Distance (Without barrier)	15 - 20M																			
Infrared induction distance	—																			
Optical Source	650nm Visible red light diode																			
Reading Precision	≥ 4mil																			
Minimum Contrast	≥ 30%																			
Decoding Capacity	UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.																			
Decoding Speed	100time/second																			
Barcode Sensitivity	Tilt	±65°																		
	Totate	±42°																		
	Deflection	±60°																		
Data interface	RJ-45																			
Mechanical and Electric Performance																				
Size(Length x Width x Height)	92.5×70×154.6 mm																			
Weight	168g																			
Indicator	Siren and LED light																			
Battery Capacity	600mah																			
Max. Power	350mw																			
Working Voltage	DC5V																			
Current	Max.Current	70ma																		
	Working Current	66ma																		
	Standby Current	45ma																		
	Sleeping Current	≤ 2ua																		
Charging Current	450ma																			
Accessory List																				
Data Cable	Micro USB																			
Wireless Receiver	—																			
CD	1																			
Operation Manual	1																			
Charge station	—																			
Environmental Parameter																				
Storage Temperature	-40°C ~ 60°C																			
Working Temperature	0°C ~ 50°C																			
Relative Humidity	0 ~ 95%																			
Height Range	1.5M																			
IP Rating	IP52																			
Certification																				
CE,RoHS,EMC,LVD, ISO9001:2008,ISO14001:2004																				

INGER CERTIFICATION ASSESSMENT SERVICES



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05
This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

Scope of approval
R&D, Production of Barcode Scanning Identification Equipment

Signed by:  Approval Date: 26 Dec. 2014
Expiry Date: 25 Dec. 2017

Manager Report Certification Information

Certification and Assessment Information

China England Accreditation Service Ltd No. 1208

Tel: +86 20 82121760

Fax: +86 20 82121761

Web: www.cas.com.cn

Add: Room 601, Jiaoling Mansion, 1208 West Zhongshan Rd., Foshan District, Guangzhou, China 510070





The certificate information can be checked on the CAS website: WWW.CAS.CN/CN. The validation of the certificate also can be obtained through www.yumite.com or by calling CAS Client Services Dept. This certificate is only valid when used together with related permits unless appropriate. This certificate holder must successfully pass yearly periodical audits to maintain the validity of the certificate after the certificate approval date. The certificate remains the property of CAS, to whom it must be returned if the management systems of the certificate holder is approved to fail to be in conformity with the certificate standard.

INGER CERTIFICATION ASSESSMENT SERVICES



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 E1 0796 R05
This is to certify the environmental management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval
The Related Environmental Management Activities of R&D, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6E, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

Signed by:  Approval Date: 26 Dec. 2014
Expiry Date: 25 Dec. 2017

Manager Report Certification Information

Certification and Assessment Information

China England Accreditation Service Ltd No. 1208

Tel: +86 20 82121760

Fax: +86 20 82121761

Web: www.cas.com.cn

Add: Room 601, Jiaoling Mansion, 1208 West Zhongshan Rd., Foshan District, Guangzhou, China 510070





The certificate information can be checked on the CAS website: WWW.CAS.CN/CN. The validation of the certificate also can be obtained through www.yumite.com or by calling CAS Client Services Dept. This certificate is only valid when used together with related permits unless appropriate. This certificate holder must successfully pass yearly periodical audits to maintain the validity of the certificate after the certificate approval date. The certificate remains the property of CAS, to whom it must be returned if the management systems of the certificate holder is approved to fail to be in conformity with the certificate standard.



Certificate of Compliance

Certificate Number: UN2014122403RC-3

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner

Trade Name : Yumite

M/N : YT-1000, YT-760, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-
M300, YT-2000, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council
RoHS Directive 2011/95/EU. It is only valid in connection with the test report number:
UN2014122403RR-3.

2014-12-24

Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongshuang Industrial Park,
Nanshan District, Shenzhen, P.R.C. 518055
Tel: +86-755-88130096 Fax: +86-755-88180138
<http://www.unt.com.cn> E-mail: info@unt.com.cn



RoHS



EC-R&TTE Certificate

Certificate Number: UN2014122403REC-1

Applicant : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Manufacturer : Shenzhen World Reputation Electronics Technology Co., Ltd.
6F, B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road,
Shilong Community, Shiyan, Bao'an District, Shenzhen

Product : Bar-code Scanner

Trade Name : Yumite

M/N : YT-1300, YT-860, YT-1200, YT-1400, YT-1600, YT-2200, YT-2300, YT-2400,
YT-2500, YT-XXXX

Essential requirement	Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a) Health	Not assessed		
Art.3.1(a) Safety	EN60950-1	UN2014122403ER-1	Pass
Art.3.1(b) EMC	ETSI EN301 489-1/3	UN2014122403ER-1	Pass
Art.3.2 Radio	ETSI EN300 440	UN2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in compliance
with the council R&TTE directive 99/5/EC. It is possible to use CE marking to demonstrate the
compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24

Date of issue

Shenzhen United Testing Technology Co., Ltd.
Room 317-319, Block 1, University Town Technology Park,
5th Zone, South Section, Hongshuang Industrial Park,
Nanshan District, Shenzhen, P.R.C. 518055
Tel: +86-755-88130096 Fax: +86-755-88180138
<http://www.unt.com.cn> E-mail: info@unt.com.cn



CE



Our factory

Yumite

