# China barcode scanner--Auto sense wired laser barcode scanner with stand YT-760B



#### Description

Semi-auto sense wired laser barcode scanner can be put on the stand and connected with POS, ATM, ticket machines and so on.



The design of Semi-auto sense wired laser barcode scanner is very humanized.

When you want to the auto-

sense only need to press the trigger for 10 seconds and then the scanner can read the barcode auto matically .

Also you can read the barcode for manual operation. so there are two kinds of function that you can





choose.

## Specification



Para	Model	YT-760B
Image		
Image		
Performance Parameter		
Depth Filed		20mm         EAN13(1Dmil,13loytes)250mm           15mm         coole39(10mil,6bytes) 260mm           40mm         coole39(15.6mil,6bytes) 350mm           15mm         coole39(15.6mil,6bytes) 270mm           20mm         15mm           20mm         coole128(10mil,6bytes) 350mm           15mm         coole128(10mil,6bytes) 350mm           20mm         100           20mm         300
Wireless Trans (without barrier	smitting Distance r)	
Infrared induction distance		150 - 200mm
Optical Source		650nm Visible red light diode
Reading Precision		≥4mil
Minimum Constract		≥ 30%
Decording Capacity		UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.
Decoding Speed		100times/second
Barcado	Tilt	±65°
Sensitivity	Rotate	±42°
Data Interface	Deflection	±60° RJ-45
		Mechanical and Electric Parameter
Size(Length x Width x Height) 92.5×70×154.6 mm		
Weight		168g
Indicator		Siren and LED Light
Battery Capaci	itv	
Max.Power		500mw
Working Voltag		DC5V
Current	Max.Current Working Current	<u>100ma</u> 92ma
	Standby Current	92ma 71ma
	Sleeping Current	
Charging Curre		450ma
		Accessory List Micro USB
Data Cable		
Wireless Receiver		
CD		
Operation Manual		1
Charge Station	1	1000 C
Holder 1set Environmental Parameter		
Storage Tempe	erature	-40°C ~ 60°C
Wireless Receiver		0°C ~ 50°C
Relative Humidity		0~95%
Height Range	alor 6	1.5M
IP Rating		IP52
Certification CE, RoHS, EMC, LVD, ISO9001:2008, ISO14001:2004		
OL, NOTO, LIVO, LYD, 1903001.2000, 19014001.2004		

#### Certification

## Yumite





#### **Our factory**

## Yumite

