Portable Mini Bluetooth Wireless CCD Barcode Scanner YT-1401MA



Description

YT-1401MA is a Mini Pocket Size Bluetooth Cordless Wireless & USB Interfaces CCD Barcode Scanner . It's a small and light weight device.

It ergonomically designed for portable use. With hand size design allow users easy carry in th e workplace.

Use 1D barcode scanning solutions with red LED barcode scanning patent. Adopt 620nm red l ight CCD imaging technology and intelligent image identification system. Integrated high perf ormance processor and decoding board, has fast decoding and high-precision reading ability, and high anti-interference ability.

Yumite barcode scanner includes various kinds barcode the scanner. Such as: wireless/wired laser barcode scanner, wireless/wired CCD barcode scanner, scanner moudle, Bluetooth barcode scanner. 2D barcode scanner, Omnidirectional barcode scanner.

Specification



Yumite

Image Performance Parameter Depth Filed Performance Parameter Unrelease transmitting distance (without barrier) Image Parameter Wireless transmitting distance (without barrier) Image Parameter Unrelease transmitting distance (without barrier) Image Parameter Unrelease transmitting distance (without barrier) Image Parameter Depth Filed Image Parameter Wireless transmitting distance (without barrier) Image Parameter Depth Filed Image Parameter Unrelease transmitting distance (without barrier) Image Parameter Depth Filed Image Parameter Unrelease transmitting distance (without barrier) Image Parameter Depth Filed Image Parameter Depth Filed Image Parameter Depth Filed Image Parameter Unrelease transmitting distance (without barrier) Image Parameter Depth Filed Image Parameter Depth Filed <th>Para</th> <th>Model</th> <th>YT-1401-MA</th>	Para	Model	YT-1401-MA
Depth Filed Depth	Image		
Serie Serie Code391156/lifebytes3 340m 90m code1281156/lifebytes3 340m 450m 00m code1281156/lifebytes3 340m 450m 00m code1281156/lifebytes3 340m 450m 00m code1281156/lifebytes3 340m 500 Wireless transmitting distance (without barrier) Itaraet induction distance			Performance Parameter
(without barrier) Its - 20W Infrared induction distance Optical Source 620nm Visible red light diode Imaging Sensor CCD Imaging Sensor CCD Reading Precision 2 5mil Minimum Contrast 2 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Tilt Rotate ±25° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) 75.4×38.5×26 mm Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Working Voltage DCSV Vorking Current 90ma Staeping Current 3ua Charging Current Accessory List Data Cable Working Current 90ma Staeping Current 3ua Charging Current Accessory List	Depth Filed		32nm code39(15.6mil,6bytes) 420mm 90nm code39(15.6mil,6bytes) 420mm 32nm code128(10mil,6bytes) 340mm 40mm code128(15.6mil,6bytes) 450mm 30mm EAN13(10mil,13bytes) 310mm 80mm EAN13(15.6mil,13bytes) 430mm
Infrared induction distance			15 - 20M
Optical Source 620nm Visible red light diode Imaging Sensor CCD Image Resolution 2500 Peixel Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UPC-AN-128, GS1 Databar, ect. Decoding Speed 280times/second Baroode Baroode Tilt ±55° Deflection ±75° Data Interface micro usb Weight 61g Indicator Siren and LED light Battery Capacity 600mah Working Voltage DC5V Working Voltage DC5V Working Current 4250ma Stadby Current 68ma Steping Current 440cma Operation Manual 1 Charging Station Working Turrent Bluetooth Current Steping Current 420cma Steping Current Accessory List Data Cable Wireless Receiver <td colspan="2"><u>.</u></td> <td></td>	<u>.</u>		
Imaging Sensor CCD Image Resolution 2500 Peixel Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Tilt Rotate ±25° Deflection ±75° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) 75.4×38.5×26 mm Weight 61g Indicator Siren and LED light Batroy Capacity 600mah Max. Power 750mw Worrking Voltage DcSV Working Current 90ma Standby Current 3ua Charging Current 3ua Charging Current 3ua Charging Current mechanical Steeping Current 3ua Charging Current Sleeping Steeping Current 3ua Charges Tation —— Wireless Receiver <			620nm Visible red light diode
Reading Precision ≥ 5mil Minimum Contrast ≥ 30% Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Barcode Sensitivity Titl Rotate ±25* Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) Vieight 61g Indicator Sizen and LED light Battery Capacity 600mah Max. Power 750mw Worrking Voltage DCSV Worrking Voltage DCSV Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 450ma Sleeping Current 3ua Charging Current 1 Operation Manual 1 Charge Temperature 40°C ~ 60°C Working Temperature Working Temperature Indicator 1 Data Cable			
Minimum Contrast ≥ 30% Decoding Capacity Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Sensitivity Tilt ±55° Deflection ±25° Detlection ±75° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) 75.4×38.5×26 mm Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Working Voltage DCSV Working Current 90ma Standby Current 3ua Signady Current Sleeping Current 450ma Sleeping Current Accessory List Data Cable Micro USB Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station —— Environment Parameter Storage Temperature 0°C ~ 60°C Working Temp			
Decoding Capacity Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar, ect. Decoding Speed 280times/second Barcode Barcode Sensitivity Tilt ±55° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) Veight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Working Voltage DCSV Max. Current 150ma Vorking Current 90ma Standby Current 3ua Charge Current Vereits Receiver Bluetooth CD 1 Operation Manual 1 Charge Temperature Environment Parameter Storage Temperature Vorking Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M			
Decoding Speed 280times/second Barcode Sensitivity Tilt ±55° Rotate ±25° Deflection ±75° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Working Voltage DCSV Working Current 150ma Working Current 68ma Sleeping Current 3ua Charging Current 450ma Sleeping Current 3ua Current Data Cable Micro USB Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Temperature Environment Parameter Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Temperat			Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar,
Barcode Barcode Sensitivity Tilt Rotate Deflection ±55° ±25° Data Interface micro usb Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) Vieta Mechanical and Electric Performance Size(Length x Width x Height) Weight Mechanical and Electric Performance Size(Length x Width x Height) Weight Mechanical and Electric Performance Size(Length x Width x Height) Weight Mechanical and Electric Performance Size(Length x Width x Height) Mechanical and Electric Performance Micro Usb Mechanical and Electric Performance Micro Usa Micro Usa Mechanical and Electric Performance Micro Usa Micro Usa Micro USB Micro USB Micro USB Micro USB			
Barcode Sensitivity Rotate Deflection ±25° ±75° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) Weight Indicator Battery Capacity Modulation Max. Corrent Morking Current Micro Usbge Current Micro USS Micro Usbge Current Micro USB Micro USB Current Advice Usb OCSV Micro USB Current Advice Usb Defactor Advice Usb OCSV Micro USB Current Advice Usb OCSV			
Sensitivity Deflection ±75° Data Interface micro usb Mechanical and Electric Performance Size(Length x Width x Height) 75.4×38.5×26 mm Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Worrking Voltage DCSV Worrking Voltage DCSV Max. Current 150ma Working Current 90ma Standby Current 3ua Clease Working Current Standby Current 3ua Charging Current Jata Cable Micro USB Environment Parameter Environment Parameter Vireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95% 0 <		a deline of the second s	
Mechanical and Electric Performance Size(Length x Width x Height) 75.4×38.5×26 mm Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Worrking Voltage DCSV Worrking Voltage DCSV Vurrent 150ma Vorrent Sieeping Current Sleeping Current 3ua Charging Current 3ua Charging Current Micro USB Data Cable Micro USB Environment Parameter Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature -40°C ~ 60°C Working Temperature Height Range 1.5M Height Range 1.5M		Deflection	
Size(Length x Width x Height) 75.4×38.5×26 mm Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Worrking Voltage DC5V Worrking Voltage DC5V Max. Current 150ma Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 450ma Data Cable Micro USB Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature Working Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52	Data Interface		
Weight 61g Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Worrking Voltage DC5V Max. Current 150ma Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 3ua Charging Current 3ua Charging Current Bluetooth Standby Current Bluetooth Standby Current 0 Standby Current 100ma Operation Manual 1 Charge Station Environment Parameter Storage Temperature Working Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Indicator Siren and LED light Battery Capacity 600mah Max. Power 750mw Working Voltage DC5V Max. Current 150ma Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 3ua Charging Current Accessory List Data Cable Micro USB Interview Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature Working Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52	and the second		CONTRACTOR DO NOT DO NOT DO NOT
Battery Capacity 600mah Max. Power 750mw Working Voltage DC5V Max. Current 150ma Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 3ua Charging Current Accessory List Data Cable Micro USB Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station —— Environment Parameter Storage Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Max. Power 750mw Working Voltage DC5V Current 150ma Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 3ua Charging Current 3ua Charging Current 3ua Charging Current Bleeping Current Jeeping Current 3ua Charging Current 450ma Data Cable Micro USB Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Worrking Voltage DC5V Lurrent 150ma Working Current 90ma Standby Current 68ma Sleeping Current 3ua Charging Current 3ua Charging Current Accessory List Data Cable Micro USB Micro USB Operation Manual 1 Operation Manual 1 Charge Station —— Environment Parameter Storage Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Max. Current 150ma Working Current 90ma Standby Current 90ma Steeping Current 3ua Charging Current 3ua Charging Current 450ma Data Cable Accessory List Data Cable Micro USB Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature Storage Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Working Current 90ma Standby Current 68ma Steeping Current 3ua Charging Current 450ma Accessory List Data Cable Micro USB Outrent Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature Working Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ° 25%) Height Range 1.5M IP Rating IP52	worrking Volt		
Standby Current 68ma Steeping Current 3ua Charging Current 3ua Charging Current 450ma Accessory List Accessory List Data Cable ————————————————————————————————————			
Sleeping Current 3ua Charging Current 450ma Accessory List Accessory List Data Cable —— Wireless Receiver Bluetooth CD 1 Operation Manual 1 Charge Station —— Environment Parameter Storage Temperature 0°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ° 25%) Height Range 1.5M IP Rating IP52		Standby Current	100 M
Accessory List Data Cable Micro USB		Sleeping Current	3ua
Micro USB	Charging Cur	rent	
University Bluetooth CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature Morking Temperature Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52	Data Cable		
CD 1 Operation Manual 1 Charge Station Environment Parameter Storage Temperature Working Temperature 0°C ~ 60°C Relative Humidity 0°C ~ 50°C Height Range 1.5M IP Rating IP52			
Operation Manual 1 Charge Station Environment Parameter Storage Temperature Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Charge Station			
Environment Parameter Storage Temperature -40°C ~ 60°C Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Working Temperature 0°C ~ 50°C Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Relative Humidity 0 ~ 95%) Height Range 1.5M IP Rating IP52			
Height Range 1.5M IP Rating IP52			
IP Rating IP52			
CE, RoHS, EMC, LVD, ISO9001:2000, ISO14001:2004			Certification

Certification

Yumite



CERTIFICATE OF REGISTRATION Certificate No.: 117 14 QU 0232-12 R05 This is to certify the quality management systems of	CERTIFICATE OF REGISTRATIO
Shenzhen World Reputation Electronics	Shenzhen World Reputation Electronics
Technology Co., LTD	Technology Co., LTD
Organization code 30608924-7	Organization code 30608924-7
Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen	Location 67, Xingqiang Commercial Mansion, No. 1 Dezbeng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen
has been assessed and registered as meeting the requirements of ISO9001:2008	has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004 Scope of approval
Stand has Approval Date: 24 Dec. 2014	The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., UTD Located in 6f, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Boom District, Shenzhen
Thereas ??	Signed by: Approval Date: 24 Dec. 201 Depiny Date: 25 Dec. 201
fear flagter handaring bling (3 he (10)	
Not increased and the second s	Ke with heating Ke with heating with the for langeled Ke with the for langeled Ke with the for langeled Ke with the for langeled

Our factory



