Snappy Reading Performance Auto-sense Laser Barcode Scanner YT-760A



Description

Yumite

Yumite auto-sense wired barcode reader is small, lightweight and its ergonomic design is comfortable to use during daily operations. It offers snappy reading performance especially on hard to read barcodes and is capable of reading a wide range of symbologies including Handsfree Stand, USB cable and IP52 Rated.

Specification



| | Model | YT-760A | | |
|--|--|--|--|--|
| | | Image | | |
| lmage | | The state of the s | | |
| | | Performance Parameter | | |
| Depth Filed | | 20mm EANI3(10mil,13loytes)250mm 15min coole39(10mil,6loytes) 260mm 15min coole39(15.6mil,6bytes) 350mm coole128(10mil,6loytes) 270mm 20min 20min EANI3(15.6mil,6loytes) 330mm EANI3(15.6mil,13loytes) 360mm 0 100 200 300 400 | | |
| Wireless Trans (without barrier | smitting Distance | | | |
| Infrared induction Distance | | 150 - 200mm | | |
| Optical Source | | 650nm Visible red light diode | | |
| Reading Percision | | ≥4mil | | |
| | root | | | |
| Minimum Conti | Webs | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal | | |
| Minimum Conti | acity | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second | | |
| Minimum Control Decoding Capa Decoding Spec | acity ed Tilt | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° | | |
| Minimum Control Decoding Capa Decoding Specification | acity ed Tilt Rotate | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second | | |
| Minimum Control Decoding Capa Decoding Specifications Barcode Sensitivity | acity ed Tilt | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface | acity ed Tilt Rotate Deflection | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface | acity ed Tilt Rotate | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x 1) Weight | acity ed Tilt Rotate Deflection | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g | | |
| Decoding Capa Decoding Specific Specif | ed Tilt Rotate Deflection Width x Height) | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm | | |
| Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power | acity ed Tilt Rotate Deflection Width x Height) | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw | | |
| Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power | acity ed Tilt Rotate Deflection Width x Height) | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to the second to the | acity ed Tilt Rotate Deflection Width x Height) | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw | | |
| Decoding Capa Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma | | |
| Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— | | |
| Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to the second | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Current Data Cable Wireless Rece | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List | | |
| Decoding Capa Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB —— —— —————————————————————————————— | | |
| Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x to the sensitivity Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man | ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———————————————————————————————————— | | |
| Decoding Capa Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD | ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second | | |
| Decoding Capa Decoding Spee Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Steeping Current ent iver | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second 165° 142° 160° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———————————————————————————————————— | | |
| Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station | ed Trilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Standby Curent ent iver | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect. 100times/second | | |
| Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic | ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% | | |
| Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x Very Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Temper Relative Humic Heigth Range | ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ———— 1Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5M | | |
| Decoding Capa Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic | ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver | ≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% | | |



CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6£ Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:







Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiong Community, Shiyan, Bao an District, Shenzhen Shenzhen Morld Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiong Community, Shiyan, Bao'an District, Shenzhen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.

2014-12-24



RoHS

Date of saue

Sherizhen United Testing Technology Co., Ltd. Boom 317-316, Block 1, University Tree Technology Fare, Sci. 97-2016. South Section, Forgranging instantial Plank. Narehard District, Streetings. PRIC 5-10009. Narehard District, Streetings. PRIC 5-10009. Tell 480-5736. Block Plank 486-50-60100190. Intel January 2018. Extenditude Section 188.





EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputations Electronics Technology Co., Ltd.
6F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Bar-code Scanner
Vivorite

Yumits YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

| Essential requirement | | Applied Specifications/Standards | Documentary Evidence | Result |
|-----------------------|--------|----------------------------------|----------------------|--------|
| Art.3.1(a) | Health | Not assessed | | |
| Art.3.1(a) | Safety | EN60950-1 | UNI20141224035R-1 | Pass |
| Art.3.1(b) | EMC | ETSI EN301 489-1/-3 | UNI2014122403ER-1 | Pass |
| A432 | Radio | ETSI EN300 440 | UNI2014122403ER-2 | Pass |

The EUT described above has been tested by us with the listed standards and found in compliance with the council RATTE directive 99/05/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24

Date of issue



Shenzhen United Testing Technology Co., Ltd.
Ruses 317-379. Bissa 1. University Trees Technology Park,
97-20ns. Good Bescon. Honorymag Industrial Park,
Nanohan Clarkit, Shendhan, PRC, 918009.
Marchan Clarki





Our factory



