# Snappy Reading Performance Auto-sense Laser Barcode Scanner YT-760A



## Description

**Yumite** 

Yumite auto-sense wired barcode reader is small, lightweight and its ergonomic design is comfortable to use during daily operations. It offers snappy reading performance especially on hard to read barcodes and is capable of reading a wide range of symbologies including Handsfree Stand, USB cable and IP52 Rated.

### **Specification**



	Model	YT-760A		
		Image		
lmage		The state of the s		
		Performance Parameter		
Depth Filed		20mm EANI3(10mil,13loytes)250mm   15min   coole39(10mil,6loytes) 260mm   15min   coole39(15.6mil,6bytes) 350mm   coole128(10mil,6loytes) 270mm   20min   20min   EANI3(15.6mil,6loytes) 330mm   EANI3(15.6mil,13loytes) 360mm   0 100 200 300 400		
Wireless Trans (without barrier	smitting Distance			
Infrared induction Distance		150 - 200mm		
Optical Source		650nm Visible red light diode		
Reading Percision		≥4mil		
	root			
Minimum Conti	Webs	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal		
Minimum Conti	acity	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second		
Minimum Control  Decoding Capa  Decoding Spec	acity ed Tilt	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65°		
Minimum Control  Decoding Capa  Decoding Specification	acity ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second		
Minimum Control  Decoding Capa  Decoding Specifications  Barcode  Sensitivity	acity ed Tilt	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45		
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate Deflection	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter		
Decoding Capa Decoding Spee Barcode Sensitivity Data Interface	acity ed Tilt Rotate	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm		
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x 1) Weight	acity ed Tilt Rotate Deflection	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second  165° 142° 160° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g		
Decoding Capa  Decoding Specific Specif	ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm		
Decoding Capa  Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity  ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw		
Decoding Capa  Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	acity  ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V		
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to the second to the	acity  ed Tilt Rotate Deflection  Width x Height)	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw		
Decoding Capa  Decoding Special Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma		
Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second  165° 142° 160° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light  —— 500mw DC5V 100ma 97ma 77ma ——		
Decoding Capa Decoding Spee Barcode Barcode Sensitivity Data Interface Weight Indicator Battery Capaci Max.Power Working Voltag	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List		
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to the second	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma		
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag Current  Charging Current  Data Cable Wireless Rece	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List		
Decoding Capa  Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB —— —— ——————————————————————————————		
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x to the sensitivity Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ————————————————————————————————————		
Decoding Capa  Decoding Speed Barcode Sensitivity Data Interface Size(Length x to Weight Indicator Battery Capacis Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second		
Decoding Capa  Decoding Spee Barcode Sensitivity Data Interface  Size(Length x to Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Current  Data Cable  Wireless Rece CD Operation Man Charge Station Holder	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Steeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second  165° 142° 160° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light  ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma  Accessory List  Mirco USB ————————————————————————————————————		
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x ) Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Curre  Data Cable Wireless Rece CD Operation Man Charge Station	ed Trilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Standby Curent ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g. China postal service code ,ect.  100times/second		
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Curre  Data Cable Wireless Rece CD Operation Man Charge Station Holder  Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%		
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface  Size(Length x Very Weight Indicator Battery Capaci Max.Power Working Voltage Current  Charging Current  Charging Current  Charging Current  Data Cable  Wireless Rece CD Operation Man Charge Station Holder  Storage Temper Relative Humic Heigth Range	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma  Accessory List  Mirco USB ———— 1Set  Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95% 1.5M		
Decoding Capa  Decoding Spece Barcode Sensitivity Data Interface Size(Length x 1) Weight Indicator Battery Capaci Max.Power Working Voltag  Current  Charging Curre  Data Cable Wireless Rece CD Operation Man Charge Station Holder  Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection  Width x Height)  ity  ge Max.Current Working Current Standby Curent Sleeping Current ent  iver	≥ 30%  UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.  100times/second ±65° ±42° ±60° RJ-45  Mechanical and Electric Parameter  92.5×70×154.6 mm  148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma  Accessory List  Mirco USB ——— 1 1 ——— 1 Set Environmental Parameter  -40°C ~ 60°C 0°C ~ 50°C 0 ~ 95%		



#### CERTIFICATE OF REGISTRATION

Certificate No.: 117 14 QU 0252-12 R05 This is to certify the quality management systems of

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of ISO9001:2008

R&D, Production of Barcode Scanning Identification Equipment

Signed by:







#### CERTIFICATE OF REGISTRATION

Shenzhen World Reputation Electronics Technology Co., LTD

Organization code 30608924-7

Location 6F, Xingqiang Commercial Mansion, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoan District, Shenzhen

has been assessed and registered as meeting the requirements of GB/T24001-2004/ISO14001:2004

Scope of approval

The Related Environmental Management Activities of RAD, Production of Barcode Scanning Identification Equipment for Shenzhen World Reputation Electronics Technology Co., LTD Located in 6£ Xingqiang Commercial Manason, No. 1 Dezheng Road, Shilong Community, Shiyan Street, Baoun District, Shenzhen

Signed by:







# Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiong Community, Shiyan, Bao an District, Shenzhen Shenzhen Morld Reputation Electronics Technology Co., Ltd. 6F, B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiong Community, Shiyan, Bao'an District, Shenzhen Bar-code Scanner

YUMBB YT-1000, YT-760A, YT-760B, YT-M200, YT-1100A, YT-1100B, YT-M300, YT-2100A, YT-2100B, YT-M400, YT-XXXX

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Drective 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.

2014-12-24



**RoHS** 

Date of saue

Sherizhen United Testing Technology Co., Ltd. Boom 317-316, Block 1, University Tree Technology Fare, Sci. 97-2016. South Section, Forgranging instantial Plank. Narehard District, Streetings. PRIC 5-10009. Narehard District, Streetings. PRIC 5-10009. Tell 480-5736. Block Plank 486-50-60100190. Intel January 2018. Extenditude Section 188.





#### **EC-R&TTE** Certificate

Certificate Number: UNIZEL4122403EC-1

Applicant

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputations Electronics Technology Co., Ltd.
6F. B Building, B Area, Xingqiang Business Building, No. 1, Dezheng Road, Shiriong Community, Shiyan, Bao an District, Shenzhen Bar-code Scanner
Vivorite

Yumits YT-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2300, YT-2400, YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

The EUT described above has been tested by us with the listed standards and found in compliance with the council RATTE directive 99/05/EC. It is possible to use CE marking to demonstrate the compliance with this Directive.

The scope of evaluation relates to the submitted documents only.

2014-12-24

Date of issue



Shenzhen United Testing Technology Co., Ltd.
Ruses 317-379. Bissa 1. University Trees Technology Park,
97-20ns. Good Bescon. Honorymag Industrial Park,
Nanohan Clarkit, Shendhan, PRC, 918009.
Marchan Clarki





**Our factory** 



