USB Automatic Induction Laser Barcode Scanner scanner with USB Cable YT-763A



Description



One of hottest sale of China Laser Barcode Scanner Reader.

- 1.Wired Barcode Scanner
- 2.Laser Barcode Scanner
- 3.Full-automatic induction
- 4. With bracket/holder/stand/DESKTOP/USB Cable
- 5. Supported PS2, RS232 and USB interface port
- 6. Wireless continous scanning or wired handheld scanning
- 7.OEM/ODM welcome

Specification



	Model	YT-760A		
		Image		
lmage				
		Performance Parameter		
Depth Filed		20mm		
Wireless Trans (without barrie	smitting Distance	_		
(without barrier) Infrared induction Distance		150 - 200mm		
Optical Source		650nm Visible red light diode		
Reading Percision		≥4mil		
Minimum Contrast Decoding Capacity		≥ 30% UPC/EAN/JAN,UPC/EAN with supplementals, UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect.		
Decoding Cap	acity	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal		
8 2 56 133	,,,	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal		
Decoding Spee	ed Tilt	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65°		
Decoding Spec	ed	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second		
Decoding Capa Decoding Specifications Barcode Sensitivity Data Interface	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code,ect. 100times/second ±65° ±42° ±60° RJ-45		
Decoding Specifications Specification Specif	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter		
Decoding Special Barcode Sensitivity Data Interface Size(Length x	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm		
Decoding Special Barcode Sensitivity Data Interface Size(Length x '	ed Tilt Rotate Deflection	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g		
Decoding Specifications Specification Specif	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage	ed Tilt Rotate Deflection Width x Height)	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw		
Decoding Special Barcode Sensitivity Data Interface Size(Length x length to	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma ——		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ———— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma		
Decoding Special Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltag Current Charging Curre Data Cable Wireless Rece	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ———— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List		
Decoding Spece Barcode Sensitivity Data Interface Size(Length x ') Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB —— —— ——		
Decoding Specific Spe	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ———— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List		
Decoding Specific Spe	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second		
Decoding Special Speci	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB —— —— 1 Set Environmental Parameter		
Decoding Spece Barcode Sensitivity Data Interface Size(Length x ' Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Statior Holder Storage Tempore	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code, ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light —— 500mw DC5V 100ma 97ma 77ma —— 450ma Accessory List Mirco USB —— 15et Environmental Parameter -40°C ~ 60°C		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnirans,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second		
Decoding Special Barcode Sensitivity Data Interface Size(Length x) Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempo Working Temp Relative Humic Heigth Range	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvarnians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second ±65° ±42° ±60° RJ-45 Mechanical and Electric Parameter 92.5×70×154.6 mm 148g Siren and LED light ——— 500mw DC5V 100ma 97ma 77ma ——— 450ma Accessory List Mirco USB ————————————————————————————————————		
Decoding Special Barcode Sensitivity Data Interface Size(Length x Weight Indicator Battery Capaci Max.Power Working Voltage Current Charging Current Charging Current Data Cable Wireless Rece CD Operation Man Charge Station Holder Storage Tempe Working Temp Relative Humic	ed Tilt Rotate Deflection Width x Height) ity ge Max.Current Working Current Standby Curent Sleeping Current ent iver	UCC/EAN128,Code39,MSI,Code11,Code39 Full ASCII, Code39 Trioptic, Code128,Code128 Full ASCII Codabar,Code93, Discrete 2 of 5 IATA,RSSvanrians,Codabar,chinese 2 of 5,Interleaved 2/5, Interleaved 2 of 5, International general dimensional barcodes, e.g.China postal service code ,ect. 100times/second		





Certificate Compliance

Certificate Number: UNIZ014123403RC-3

Shenzhen World Reputation Electronics Technology Co., Ltd.
6f. Bluiding, B Area, Xingqiang Business Building, No. 1, Dezheng Road,
Shiong Community, Shiyan, Seo an District, Shenzhen
Shenzhen World Reputation Electronics Technology Co., Ltd.
6f. Bluiding, B Area, Xingqiang Business Building, No. 1, Dezheng Road,
Shiong Community, Shiyan, Bao'an District, Shenzhen
Bar-code Scanner

Test Standard: IEC62321:2013

The EUT described above has been consolidated by us and found in compliance with the council RoHS Directive 2011/95/EU. It is only valid in connection with the test report number: UNI2014122403RR-3.





RoHS



Sheruhen United Testing Technology Co., Ltd.





EC-R&TTE Certificate

Certificate Number: UNIZEL4122403EC-1

Shenzhen World Reputation Electronics Technology Co., Ltd.
5F. B Building, B Area, Xingqiang Business Building, No.1, Dezheng Road, Shirlong Community, Shiyan, Bao an District, Shenzhen Shenzhen World Reputation Electronic

| Bar-code Scanner | Yumite | Y1-1300, YT-880, YT-1200, YT-1400, YT-1500, YT-2200, YT-2200, YT-2400, | YT-2500, YT-XXXX

Essential requirement		Applied Specifications/Standards	Documentary Evidence	Result
Art.3.1(a)	Health	Not assessed		
Art.3.1(a)	Safety	EN60950-1	UNI20141224035R-1	Pass
Art.3.1(b)	EMC	ETSI EN301 489-1/-3	UNI2014122403ER-1	Pass
A432	Radio	ETSI EN300 440	UNI2014122403ER-2	Pass

with the council R&TTE directive 90/5/EC. It is possible to use CE marking to demonstrate the compliance with this Directive. The scope of evaluation relates to the submitted documents only.

2014-12-24





Shenzhen United Testing Technology Co., Ltd.





Application

2014-12-24

Date of saue



