

Printer Parameters:

Item Parameters

Print parameters Printing Method Thermal Line

Printing width 72mm

Resolution 576 Dots/Line or 512 Dots/Line [8dots/mm] [203dpi]

Print speed 300mm/Second(Max)

Interface USB,Internet,Internet+USB+COM,Internet+USB+WIFI,USB+COM,USB+Bluetooth,USB+WIFI

Line Spacing 3.75mm [Can adjust line spacing by command]

Line No. FontA-48Lines/FontB-64Lines

Character Size ANK character [Font A] [1.5×3.0mm] [12×24 dots]

Font B [1.1×2.1mm] [9×17 dots]

Bar code Character Extended character set

PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)

Bar code 1D bar code [UPC-A/UPC-

E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128

2D barcode [QR CODE]

Graphics printing Graphics printing Supports bitmap download and print

Cutter Cutter Function Full cut/Half cut

Paper Type Thermal

Width 79.5±0.5mm

Diameter ≤80mm

Feed method Easy feed(Clameshell feed)

Print commands Commands ESC/POS

Power Power Adaptor Input [AC 100V-240V,50-60Hz

Output [DC 24V/2.5A

Cash Drawer output DC 24V/1A

Buffer Input Buffer 2048K bytes

NV Flash 256K bytes

physical characteristics Weight 1.3KG

Dimension 198*148*148(MM)

environment Working Temp [5 ~ 45°C] Humidity [10 ~ 80%

Storage Temp [-10 ~ 50°C] Humidity [10 ~ 90%] No dew

Reliability parameter Print Head Life 150KM [print density ≤12.5]

Cutter Life 1500,000times

Software Driver Android,IOS,Linux,,Windows

