

Printer Parameters:

Item Parameters

Print parameters Printing Method Thermal Line

Printing width 72mm

Resolution 576 Dots/Line or 512 Dots/Line□8dots/mm□203dpi□

Print speed 300mm/Second

Interface USB,Internet,Internet+USB+COM,Internet+USB+WIFI,USB+COM,USB+Bluetooth,USB+WIFI

Line Spacing 3.75mm□Can adjust line spacing by command□

Line No. FontA-48Lines/FontB-64Lines

Character Size ANK character□Font A□1.5×3.0mm□12×24 dots□

Font B□1.1×2.1mm□9×17 dots□

Bar code Character Extended character set

PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)

Bar code 1D bar code□UPC-A/UPC-

E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128

2D barcode□QR CODE

Graphics printing Graphics printing Supports bitmap download and print

Cutter Cutter Function Full cut/Half cut

Paper Type Thermal

Width 79.5±0.5mm

Diameter ≤80mm

Feed method Easy feed(Clameshell feed)

Print commands Commands ESC/POS

Power Power Adaptor Input□AC 100V-240V,50-60Hz

Output□DC 24V/2.5A

Cash Drawer Output DC 24V/1A

Buffer Input Buffer 2048K bytes

NV Flash 256K bytes

physical characteristics Weight 1.15KG

Dimension 195*140*148(MM)

environment Working Temp□5 ~ 45°C□ Humidity□10 ~ 80%

Storage Temp□-10 ~ 50°C □Humidity□10 ~ 90%□No dew□

Reliability parameter Print Head Life 150KM□print density≤12.5□

Cutter Life 1500,000times

Software Driver Android,IOS,Linux,,Windows

