YT-1101B handheld semi-auto sense CCD barcode scanner with stand

Description

YT-1101B is semi-auto sense wired CCD barcode scanner which can be put on the stand and connected with POS ,ATM ,ticket machines and so on.

Function

the design of YT-1101B is very humanized.when you want to the auto-sense only need to press the trigger for 10 seconds and then the scanner can read the barcode automatically .also you can read the barcode for manual operation. so there are two kinds of function that you can choose.

Specification





Yumite

| Para | Model | YT-1101B |
|--|------------------------------------|--|
| | | Image |
| Image | | |
| | | Performance Parameter |
| Depth Filed | | 32nn code39(10nil,6bytes)310mn 32nn code39(15.6nil,6bytes) 420mn 32nn code39(15.6nil,6bytes) 420mn 32nn code39(15.6nil,6bytes) 420mn 32nn code128(10nil,13bytes) 340nn 30nn EANI3(10nil,13bytes) 310nn 80nn EANI3(15.6nil,13bytes) 430nn 0 100 200 300 400 500 |
| Wireless Transmitting Distance | | |
| (without barrier) Infrared induction distance | | 150 - 200mm |
| Optical Source | | 620nm Visible red light diode |
| Imaging Sensor | | CCD |
| Image Resolution | | 2500Pixel |
| Reading Precision Minimum Contrast | | ≥ 5mil |
| Decoding Capacity | | ≥ 30% Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar, Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar,ect. |
| Decoding Speed | | 280time/second |
| Barcode | Tile | ±55° |
| Barcode Sensitivity | Rotate | ±25° |
| Data Interface | Deflection | ±75° RJ-45 |
| | | Mechanical and Electric Performance |
| Size(Length x Width x Height) | | 92.5×70×154.6 mm |
| Weight | | 140g |
| Indicator | | Visible red light diode |
| Battery Capacity Max.Power | | |
| Working Voltage | | 500mw DC5V |
| , ond | Max.Current | 100ma |
| Vorking Voltag | Working Current Standby Current | 89ma |
| | Standby Current Standby Current | 47ma |
| Charging Curre | ent | |
| Charging Time | | |
| A fully charged readable barcode | | Accessory List |
| Data Cable | | Micro USB RS232 Cable |
| Wireless Receiver | | |
| CD Operation Manual | | 1 |
| Charge Station | | <u>1997</u> |
| Holder | | 1Set |
| Storage Tam | oraturo | Environment Parameter |
| Storage Temperature Working Temperature | | -40°C ~ 60°C 0°C ~ 50°C |
| Relative Humidity | | 0~95% |
| Height Range | | 2M |
| IP Rating | | IP52 Certification |
| CE,RoHS,EMC,LVD+ ISO9001:2008,ISO14001:2004 | | |