

Wireless Transmitting Distance (without barrier) ——
Infrared induction distance 150 - 200mm
Optical Source 620nm Visible red light diode
Imaging Sensor CCD
Resolution Ratio 2500 pixel
Image Resolution $\geq 5\text{mil}$
Minimum Contrast $\geq 30\%$
Barcode Types "Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar,
Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar etc."
Decoding Speed 280times/second
Barcode Sensitivity Tilt $\pm 55^\circ$
Rotate $\pm 25^\circ$
Deflection $\pm 75^\circ$
Data Interface Port RJ-45
Mechanical and Electric Performance
Size (Length x Width x Height) 92.5×70×154.6 mm
Weight 140g
Indicator Siren and LED light
Max. Power 500mw
Working Voltage DC5V
Current Max. Current 100ma
Working Current 89ma
Stand-by Current 47ma
Sleeping Current ——
Accessory List
Data line USB data line (1.8m)
RS232 data line (1.8m)
Receiver ——
Drive CD ——
Operation Manual 1 Piece
stand 1 Piece
Environmental Parameter
Storage Temperature $-40^\circ\text{C} \sim 60^\circ\text{C}$
Working Temperature $0^\circ\text{C} \sim 50^\circ\text{C}$
Relative Humidity 0 ~ 95%
Height Range 2m
IP Rating IP52

Certificates:

CE, RoHS, EMC, LVD □ ISO9001:2008 □ ISO14001:2004

