

Wireless Transmitting Distanc (without barrier) 300 - 400m
Infrared induction distance ——
Optical Source 620nm Visible red light diode
Imaging Sensor CCD
Resolution Ratio 2500 pixel
Image Resolution $\geq 5\text{mil}$
Minimum Contrast $\geq 30\%$
Barcode Types "Code128, EAN-13, EAN-8, Code39,UPC-A, UPC-E, Codabar,
Interleaved 2 of 5,ISBN, Code 93, UCC/EAN-128, GS1 Databar etc."
Decoding Speed 300times/second
Barcode Sensitivity Tilt $\pm 55^\circ$
Rotate $\pm 25^\circ$
Deflection $\pm 75^\circ$
Data Interface Port RJ-45
Mechanical and Electric Performance
Size(Length x Width x Height) 210×84×117.5 mm
Weight 320g□Include Cradle□
Indicator Siren and LED light
Battery Capacity 600mah
Max.Power 750mw
Working Voltage DC5V
Current Max.Curren 150ma
Working Current 90ma
Stand-by Current 68ma
Sleeping Current 3ua
Charging Current 450ma
Accessory List
Data line USB Charging Line
——
Drive CD ——
Operation Manual 1Piece
Charging Cradle 1Piece
Environmental Parameter
Storage Temperature $-40^\circ\text{C} \sim 60^\circ\text{C}$
Working Temperature $0^\circ\text{C} \sim 50^\circ\text{C}$
Relative Humidity 0 ~ 95%
Height Range 1.5m
IP Rating IP52

Certificates:

CE,RoHS,EMC,LVD□ISO9001:2008□ISO14001:2004

