

Optical Source 620nm Visible red light diode

Imaging Sensor CMOS

resolution ratio 752*480

Image Resolution $\geq 5\text{mil}$

Minimum Contrast $\geq 30\%$

Barcode Types 2D "PDF417, microQR,QR Code(Model 1/2), Data Matrix(ECC200, ECC000,050, 080, 100,140)etc."

1D "Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, etc."

Decoding Speed 300times/second

Barcode Sensitivity Tilt $\pm 55^\circ$

Rotate $\pm 25^\circ$

Deflection $\pm 75^\circ$

Data Interface Port RJ-45

Mechanical and Electric Performance

SIZE(Length x Width x Height) 92.5×70×154.6 mm

Net Weight 140g

Indicator Siren and LED light

Max.Power 1750mw

Working Voltage DC5V

Current Max.Current 350ma

Working Current 325ma

Stand-by Current 53ma

Accessory

Data Cable One USB Line , RS232

Operation Manual One

Environmental Parameter

Storage Temperature $-40^\circ\text{C} \sim 60^\circ\text{C}$

Working Temperature $0^\circ\text{C} \sim 50^\circ\text{C}$

Relative Humidity 0 ~ 95%

Height range 2M

IP Rating 2.54mm flex cable□1.2m□

Certificates

CE,RoHS,EMC,LVD□ISO9001:2008□ISO14001:2004

Yumite



CE



Yumite



CE



Yumite



CE



Yumite



CE



Yumite



CE

