

Wireless Transmitting Distance (without barrier) ——
Infrared induction distance 150 - 200mm
Optical Source 650nm Visible red light diode
Image Resolution $\geq 4\text{mil}$
Minimum Contrast $\geq 30\%$
Barcode Types "UPC/EAN/JAN, UPC/EAN with supplementals
UCC/EAN128, Code39, MSI, Code11, Code39 Full ASCII,
Code39 Trioptic, Code128, Code128 Full ASCII Codabar, Code93,
Discrete 2 of 5 IATA, RSSvanrians, Codabar, chinese 2 of 5, Interleaved 2/5,
Interleaved 2 of 5, International general dimensional barcodes"

Decoding Speed 100times/s
Barcode Sensitivity Tilt $\pm 65^\circ$
Rotate $\pm 42^\circ$
Deflection $\pm 60^\circ$
Data Interface Port RJ-45
Mechanical and Electric Performance
Size (Length x Width x Height) 92.5×70×154.6 mm
Weight (except cable) 148g
Indicator Siren and LED light
Battery Capacity ——
Max. Power 500mw
Working Voltage DC5V
Current Max. Current 100ma
Working Current 97ma
Stand-by Current 77ma
Sleeping Current ——
Charging Current 450ma

Accessory List
Data line USB data line(1.8m)
RS232 data line(1.8m)
Receiver ——
Drive CD ——
Operation Manual 1 Piece
Charging Cradle ——
Stand 1 Set
Environmental Parameter
Storage Temperature $-40^\circ\text{C} \sim 60^\circ\text{C}$
Working Temperature $0^\circ\text{C} \sim 50^\circ\text{C}$
Relative Humidity 0 ~ 95%
Height Range 1.5m
IP Rating IP52

Certificates :

CE, RoHS, EMC, LVD, ISO9001:2008, ISO14001:2004







