

Wireless Transmitting Distance (without barrier) ——
 Infrared induction distance 150 - 200mm
 Optical Source 650nm Visible red light diode
 Image Resolution $\geq 4\text{mil}$
 Minimum Contrast $\geq 30\%$
 Barcode Types "UPC/EAN/JAN, UPC/EAN with supplementals
 UCC/EAN128, Code39, MSI, Code11, Code39 Full ASCII,
 Code39 Trioptic, Code128, Code128 Full ASCII Codabar, Code93,
 Discrete 2 of 5 IATA, RSS variants, Codabar, chinese 2 of 5, Interleaved 2/5,
 Interleaved 2 of 5, International general dimensional barcodes"
 Decoding Speed 100times/s
 Barcode Sensitivity Tilt $\pm 65^\circ$
 Rotate $\pm 42^\circ$
 Deflection $\pm 60^\circ$
 Data Interface Port RJ-45
 Mechanical and Electric Performance
 Size (Length x Width x Height) 92.5×70×154.6 mm
 Weight (except cable) 148g
 Indicator Siren and LED light
 Battery Capacity ——
 Max. Power 500mw
 Working Voltage DC5V
 Current Max. Current 100ma
 Working Current 97ma
 Stand-by Current 77ma
 Sleeping Current ——
 Charging Current 450ma
 Accessory List
 Data line USB data line(1.8m)
 RS232 data line(1.8m)
 Receiver ——
 Drive CD ——
 Operation Manual 1 Piece
 Charging Cradle ——
 Stand 1 Set
 Environmental Parameter
 Storage Temperature $-40^\circ\text{C} \sim 60^\circ\text{C}$
 Working Temperature $0^\circ\text{C} \sim 50^\circ\text{C}$
 Relative Humidity 0 ~ 95%
 Height Range 1.5m
 IP Rating IP52

Certificates :

CE, RoHS, EMC, LVD □ ISO9001:2008 □ ISO14001:2004







